

## Table of Contents



```

ALTER PROCEDURE [dbo].[xml_core_SISSE_webshop] AS
DECLARE @klient_kood bigint, @kood bigint, @nimitmp nvarchar(255), @addrtmp
nvarchar(255), @konttmp nvarchar(255), @koodid varchar(1000)
declare @ladu nvarchar(32), @seeria nvarchar(32), @objekt nvarchar(32), @s1
int, @s2 int, @webid nvarchar(32), @webtype nvarchar(32)
declare @number int, @maa int, @kmk nvarchar(32), @x int, @kinnitatud int
DECLARE @myyja nvarchar(32), @aeg datetime
declare @key nvarchar(32), @appkey nvarchar(64), @appkey_setting
nvarchar(64)
declare @result1 xml, @result2 nvarchar(max)
declare @artikel nvarchar(32), @id_exist int
declare @kl_kood nvarchar(32), @nimi nvarchar(255), @kustuta int
declare @ag datetime
declare @err nvarchar(32)
select @ag =getdate()
set @key=CONVERT(nvarchar,getdate())
update in_webshop_tell_tellimused set x=@key where x is null
update xml_in_imago_tellimused set x=@key where x is null
set @koodid=''

select @appkey_setting=setting from settings where ID='xmlcore_key'

create table #results
(number nvarchar(32), ttyp nvarchar(32), result int, descr nvarchar(255),
submittype nvarchar(32))

--vastuvotmine, kogused
--SELECT * FROM in_webshop_tell_tellimused WHERE number = '2000117'
-- DELETE FROM in_webshop_tell_tellimused WHERE number = '2000117'
-- UPDATE in_webshop_tell_tellimused SET x = null WHERE number = '2000117'
-- EXEC [dbo].[xml_core_SISSE_webshop]

--sales order from E-agent [LV software]
declare tellimused cursor for select number, appkey from
in_webshop_tell_tellimused with(nolock) where x=@key
open tellimused
FETCH NEXT FROM tellimused INTO @webid, @appkey
WHILE @@FETCH_STATUS = 0
BEGIN
    if ISNULL(@appkey,'')!=ISNULL(@appkey_setting,'')
    begin
        insert into #results values (@appkey, 'ORDER', 1, 'Incorrect
key','Orders')

        end
        else
        begin

            select @id_exist=count(*) from tell_tellimused with(nolock) where

```

```
number=@webid
    if @id_exist=0
    BEGIN
        set @number=@webid
        select @maa=maa from kliendid with(nolock) where kood=(select
klient_kood from in_webshop_tell_tellimused with(nolock) where
number=@number)

            insert into tell_tellimused (number, myyja, aeg, klient_kood,
arvetasub, tingimus, ladu, klient_nimi, lahetusviis
                , kommentaar, valuuta, kurssbvl
                , esindaja, telefon, aadress1, aadress2, aadress3
                , lahetusaadress1, lahetusaadress2, lahetusaadress3
                , klient_nimi_lahetusel
                , ts, cu, Field57, objekt
                , hinnakiri, lahetusaeg, lisa_field1
                )
            SELECT @number
            ,ISNULL(myyja, 'XML')
            , aeg
            , klient_kood
            , isnull((select top 1 arvetasub from kliendid where
kood=klient_kood),arvetasub)
            , isnull(tingimus,(select TOP 1 tingimus from kliendid
with(nolock) where kood=klient_kood))
            , isnull(ladu,'GAL')
            , isnull(klient_nimi,(select TOP 1 nimi from kliendid
with(nolock) where kood=klient_kood))
            , isnull(tingimus,(select TOP 1 tingimus from kliendid
with(nolock) where kood=klient_kood))
            ,kommentaar
            , 'EUR', 1
            , isnull(esindaja,(select TOP 1 kontakt from kliendid
with(nolock) where kood=klient_kood))
            , isnull(telefon,(select TOP 1 telefon from kliendid
with(nolock) where kood=klient_kood))
            , isnull(aadress1,(select TOP 1 aadress1 from kliendid
with(nolock) where kood=klient_kood))
            , isnull(aadress2,(select TOP 1 aadress2 from kliendid
with(nolock) where kood=klient_kood))
            , isnull(aadress3,(select TOP 1 aadress3 from kliendid
with(nolock) where kood=klient_kood))
            , isnull(lahaaddress1,(select TOP 1 lahaaddress1 from kliendid
with(nolock) where kood=klient_kood))
            , isnull(lahaaddress2,(select TOP 1 lahaaddress2 from kliendid
with(nolock) where kood=klient_kood))
            , isnull(lahaaddress3,(select TOP 1 lahaaddress3 from kliendid
with(nolock) where kood=klient_kood))
            , isnull(klientnimi_lahetusel,(select TOP 1 nimi_lahetusel
from kliendid v where kood=klient_kood))
```

```
, GETDATE(), 'XML'
    , isnull(email,(select TOP 1 email from kliendid
with(nolock) where kood=klient_kood))
        , isnull(objekt,(select TOP 1 objekt from kliendid
with(nolock) where kood=klient_kood))
            ,(select TOP 1 hinnakiri from kliendid with(nolock) where
kood=klient_kood)
                , lahetusaeg
                , isnull(lisa_field1,(select TOP 1 sisu from yld_data
with(nolock) where kood='TRANSPORTER' AND KLASS='KLIENT' AND
kaart=klient_kood))
                    FROM in_webshop_tell_tellimused with(nolock) where
number=@number

-- UPDATE in_tell_tellimused_read SET artikkel = ISNULL((select
artikkel from artiklid_hankija_artiklid with(nolock) where hankija_artikkel
= in_tell_tellimused_read.artikkel),artikkel) WHERE NOT EXISTS(SELECT top 1
kood FROM artiklid WITH(nolock) WHERE kood =
in_tell_tellimused_read.artikkel)

insert into tell_tellimused_read
(number,yhik, artikkel, variant, konto, kogus, field8,
yhikuhind, summa, ostuhind, nimetus, kmkood, r_kommentaar, rn, rv)
select @number
, isnull((select top 1 yhik from artiklid where
kood=artikkel),'gb')
, artikkel
,variant
, isnull((select konto_myyk from artiklid where
kood=in_webshop_tell_tellimused_read.artikkel),(select TOP 1 myyk_eestis
from artikliklassid with(nolock) where kood=(select TOP 1 klass from
artiklid where kood=artikkel)))
, kogus
, case
when EXISTS (select top 1 ale from mr_hinnavalemid_read
with(nolock) where mida='8' and kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number) and ((select aeg from
tell_tellimused with(nolock) where number=@number) between aegl and aeg2 )
and in_webshop_tell_tellimused_read.artikkel=artikkel or mida='8' and
kood=(select top 1 hinnakiri from tell_tellimused with(nolock) where
number=@number) and(aegl is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkel=artikkel)
then
('0')

when ((select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aegl and aeg2 )) is NOT null)
then (select top 1 ale from mr_hinnavalemid_read where
```

```

mr_hinnavalemid_read.artikkeli =in_webshop_tell_tellimused_read.artikkeli and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 ))


when ((select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkeli =in_webshop_tell_tellimused_read.artikkeli and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and AEG1 IS NULL AND AEG2 IS NULL) is NOT null)
    then (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkeli =in_webshop_tell_tellimused_read.artikkeli and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) AND aeg1 IS NULL and aeg2 IS NULL )

        --when ((select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkeli =in_webshop_tell_tellimused_read.artikkeli and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 )) is null
            --and (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkeli =in_webshop_tell_tellimused_read.artikkeli and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and (aeg1 is NOT null and aeg2 is NOT null ) AND
((select top 1 AEG from tell_tellimused with(nolock) where number=@number)
between AEG1 AND AEG2)) is not null)
                --then (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkeli =in_webshop_tell_tellimused_read.artikkeli and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and (aeg1 is NOT null and aeg2 is NOT null ) AND
((select top 1 AEG from tell_tellimused with(nolock) where number=@number)
between AEG1 AND AEG2))

                    when
                        ((select top 1 ale from mr_hinnavalemid_read
                            inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkeli
                            inner join tell_tellimused ON
tell_tellimused.number=@number
                            where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
                            and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
                            and
                            ((tell_tellimused.aeg) between mr_hinnavalemid_read.aeg1
and mr_hinnavalemid_read.aeg2 )) is not null)
                            then (select top 1 ale from mr_hinnavalemid_read
                                inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkeli
                                inner join tell_tellimused ON
tell_tellimused.number=@number
                                where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'

```

```
        and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
        and
        ((tell_tellimused.aeg) between mr_hinnavalemid_read.aeg1
and mr_hinnavalemid_read.aeg2 ))
        when ((select top 1 ale from mr_hinnavalemid_read
inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkeli
inner join tell_tellimused ON
tell_tellimused.number=@number
where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
        and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
        and
        ((tell_tellimused.aeg) between mr_hinnavalemid_read.aeg1
and mr_hinnavalemid_read.aeg2 )) is null and (select top 1 ale from
mr_hinnavalemid_read
inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkeli
inner join tell_tellimused ON
tell_tellimused.number=@number
where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
        and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
        and
        (mr_hinnavalemid_read.aeg1 is null and
mr_hinnavalemid_read.aeg2 is null )) is not null)
        then (select top 1 ale from mr_hinnavalemid_read
inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkeli
inner join tell_tellimused ON
tell_tellimused.number=@number
where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
        and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
        and
        (mr_hinnavalemid_read.aeg1 is null and
mr_hinnavalemid_read.aeg2 is null )) END
        -- when
        -- ((select top 1 ale from mr_hinnavalemid_read
        -- inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkeli
        -- where mr_hinnavalemid_read.klass=artiklid.klass
        -- and
        -- ((select aeg from tell_tellimused with(nolock) where
number=@number) between aeg1 and aeg2)) is null and (select top 1 ale from
mr_hinnavalemid_read inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkeli where
```

```

mr_hinnavalemid_read.klass=artiklid.klass and (aeg1 is null and aeg2 is
null)) is not null)
    -- then (select top 1 ale from mr_hinnavalemid_read inner
join artiklid ON artiklid.kood=in_webshop_tell_tellimused_read.artikkeli
where mr_hinnavalemid_read.klass=artiklid.klass and (aeg1 is null and aeg2
is null))END
    -- ,case when EXISTS (select top 1 ale from mr_hinnavalemid_read
with(nolock) where mida='8' and kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number) and ((select aeg from
tell_tellimused with(nolock) where number=@number) between aeg1 and aeg2 )
and in_webshop_tell_tellimused_read.artikkeli=artikkeli or mida='8' and
kood=(select top 1 hinnakiri from tell_tellimused with(nolock) where
number=@number) and(aeg1 is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkeli=artikkeli)
    -- then
        -- '0'
-- ELSE
    -- isnull((select top 1 ale from mr_hinnavalemid_read with(nolock) where
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 ) and
in_webshop_tell_tellimused_read.artikkeli=artikkeli or mida='0' and
kood=(select top 1 hinnakiri from tell_tellimused with(nolock) where
number=@number) and(aeg1 is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkeli=artikkeli),
    -- isnull((select top 1 ale from mr_hinnavalemid_read with(nolock)
where mida='0' and kood=(select top 1 hinnakiri from tell_tellimused
with(nolock) where number=@number) and ((select aeg from tell_tellimused
with(nolock) where number=@number) between aeg1 and aeg2 ) and klass=(select
top 1 klass from artiklid where
kood=in_webshop_tell_tellimused_read.artikkeli),(select top 1 ale from
mr_hinnavalemid_read with(nolock) where mida='0' and kood=(select top 1
hinnakiri from tell_tellimused with(nolock) where number=@number) and(aeg1
is null and aeg2 is null) and klass=(select top 1 klass from artiklid where
kood=in_webshop_tell_tellimused_read.artikkeli)))
    -- END
        -- , isnull((select top 1 ale from mr_hinnavalemid_read
where mida='8' and artikkeli=(select top 1 artikkeli from
in_webshop_tell_tellimused_read where
in_webshop_tell_tellimused_read.artikkeli=artikkeli) and (((select aeg from
tell_tellimused where number=@number) between aeg1 and aeg2 ) or (aeg1 is
null and aeg2 is null)) and kood=(select hinnakiri from tell_tellimused
where number=@number)), 0)
        -- , isnull(hind,(select dbo.get_hind6(artikkeli,(SELECT top
1 hinnakiri from tell_tellimused INNER JOIN mr_hinnavalemid_read ON
mr_hinnavalemid_read.artikkeli=artikkeli and mida='8' and (((select aeg from
tell_tellimused where number=@number) between aeg1 and aeg2 ) or (aeg1 is
null and aeg2 is null)) where number=@number), null, null, null,null,
null,null, null, null,null,0)))
            ,case when EXISTS (select top 1 ale from

```

```

mr_hinnavalemid_read with(nolock) where mida='8'
    and kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
        and ((select aeg from tell_tellimused
with(nolock) where number=@number) between aeg1 and aeg2 )
            and
in_webshop_tell_tellimused_read.artikkeli=artikkeli
                or mida='8' and kood=(select top 1
hinnakiri from tell_tellimused with(nolock) where number=@number) and(aeg1
is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkeli=artikkeli)
            then
                (select dbo.get_hind6(artikkeli,(SELECT top 1 hinnakiri
from tell_tellimused where number=@number), null, null ,null,null,
null,null, (select top 1 aeg from tell_tellimused where number=@number),
null,null,0))

ELSE

(select top 1 baashind from artiklid where
kood=in_webshop_tell_tellimused_read.artikkeli)
    END
        , kogus*isnull(hind,(select top 1 baashind from artiklid
with(nolock) where kood=artikkeli))*(100-ISNULL(ale,0))/100
        , dbo.kesk_hind(artikkeli,getdate())
        , isnull(nimetus,(select top 1 nimi from artiklid
with(nolock) where kood=artikkeli))
        , isnull((select top 1 kmkood from artiklid with(nolock)
where kood=artikkeli),(select top 1 kmk_eesti from artikliklassid
with(nolock) where kood=(select TOP 1 klass from artiklid where
kood=artikkeli)))
        ,kommentaar, ROW_NUMBER() OVER(ORDER BY rn) , ROW_NUMBER()
OVER(ORDER BY rn )
        FROM in_webshop_tell_tellimused_read with(nolock) where
number=@number

        update tell_tellimused_read
        set kmkood=ISNULL((select top 1 KMkood from artiklid
with(nolock) where kood=tell_tellimused_read.artikkeli),(select kmk_eesti
from artikliklassid with(nolock) where kood=(select top 1 klass from
artiklid with(nolock) where kood=tell_tellimused_read.artikkeli)))
        where number=@number and kmkood is null
        UPDATE tell_tellimused_read set tkkm = dbo.summaKM
(yhikuhind,kmkood), rsum = dbo.summaKM(summa,kmkood)      where number=@number

        update tell_tellimused_read
        set konto=ISNULL((select top 1 konto_myyk from artiklid
with(nolock) where kood=tell_tellimused_read.artikkeli),(select myyk_eestis
from artikliklassid with(nolock) where kood=(select top 1 klass from
artiklid with(nolock) where kood=tell_tellimused_read.artikkeli)))
        where number=@number and konto is null

```

```

--EXEC dbo.tell_tellimused_renum @number
EXEC dbo.arvuta_tellimus @number
update tell_tellimused_read set rv=rn where number=@number
exec hooldus_vaba 'tellimus',@number
set @koodid=@koodid+convert(nvarchar,@number)
insert into kliendid (kood, nimi, aadress1, aadress2, aadress3,
nimi_lahetusel, lahaadress1, lahaadress2, lahaadress3
, kontakt, email, telefon
,klient_tyyp, klass, regnr, kliendikaart
,cu,ts)
select top 1
klient_kood, klient_nimi, aadress1, aadress2, aadress3,
klientnimi_lahetusel, lahaadress1, lahaadress2, lahaadress3
, esindaja,email,telefon
,klient_tyyp, klient_klass, klient_regnr, klient_kliendikaart
,'XML',GETDATE()
FROM in_webshop_tell_tellimused with(nolock) where
number=@number
and ISNULL(klient_kood,'')!=''
and klient_kood not in (select kood from kliendid with(nolock))
insert into #results values (@webid, 'ORDER', 0, 'OK','Orders')
end
ELSE
BEGIN
    insert into #results values (@webid, 'ORDER', 2,
'Duplicate','Orders')
END

        set @x=@x+1
end
FETCH NEXT FROM tellimused INTO @webid, @appkey
if @@FETCH_STATUS = 0 set @koodid=@koodid+';
END
CLOSE tellimused
DEALLOCATE tellimused

--cleanup
--delete from in_webshop_tell_tellimused_klient where number in (select
number from in_webshop_tell_tellimused where x=@key)

delete from in_webshop_tell_tellimused_read where number in (select number
from in_webshop_tell_tellimused where x=@key)
delete from in_webshop_tell_tellimused where x=@key

-----
-----
-----
--sales orders from imago [EE software]

```

```
--vastuvotmine, kogused
declare tellimused cursor for select number, appkey from
xml_in_imago_tellimused where x=@key
open tellimused
FETCH NEXT FROM tellimused INTO @webid, @appkey
WHILE @@FETCH_STATUS = 0
BEGIN
    if ISNULL(@appkey,'')!=ISNULL(@appkey_setting,'')
    begin
        insert into #results values (@appkey, 'ORDER', 1, 'Incorrect
key','Orders')

    end
    else
    begin

        select @id_exist=count(*) from tell_tellimused where
kliendi_tellimus=convert(nvarchar(max),@webid)
        if @id_exist=0
        BEGIN
            --set @number=@webid
            EXEC dbo.get_dok_number @moodul='tellimus',@seeria='DOC',@NUMBER
= NULL, @cu='xmlcore', @aeg=@ag, @keel = 'default', @num =@number OUTPUT,
@aerr = @err OUTPUT

            update tell_tellimused set
myyja=iif(isnull(z.myyja,'')!='',z.myyja,iif(isnull((select myyja from
kliendid where kood=z.arvetasub),'')!='',(select myyja from kliendid where
kood=z.arvetasub),iif(isnull((select myyja from kliendid where
kood=z.klient_kood),'')!='',(select myyja from kliendid where
kood=z.klient_kood),'XML'))),
aeg=z.aeg,
klient_kood=z.klient_kood,
arvetasub=z.arvetasub,
tingimus=isnull(z.tingimus,(select tingimus from
kliendid where kood=z.klient_kood)),
ladu=isnull(z.ladu,'GAL'),
klient_nimi=isnull(z.klient_nimi,(select nimi from
kliendid where kood=z.klient_kood)),
lahetusviis=isnull(z.tingimus,(select tingimus from
kliendid where kood=z.klient_kood)),
kommentaar=z.kommentaar,
valuuta='EUR',
kurssbvl=1,
esindaja=isnull(z.esindaja,(select kontakt from kliendid
where kood=z.klient_kood)),
telefon=isnull(z.telefon,(select telefon from kliendid
where kood=z.klient_kood)),
aadress1=isnull(z.aadress1,(select aadress1 from
kliendid where kood=z.klient_kood)),
aadress2=isnull(z.aadress2,(select aadress2 from
```

```

kliendid where kood=z.klient_kood),
           aadress3=null(z.aadress3,(select aadress3 from
kliendid where kood=z.klient_kood),
           lahetusaadress1=null(z.lahaaddress1,(select lahaaddress1
from kliendid where kood=z.klient_kood)),
           lahetusaadress2=null(z.lahaaddress2,(select lahaaddress2
from kliendid where kood=z.klient_kood)),
           lahetusaadress3=null(z.lahaaddress3,(select lahaaddress3
from kliendid where kood=z.klient_kood)),
klient_nimi_lahetusel=null(z.klientnimi_lahetusel,(select nimi_lahetusel
from kliendid where kood=z.klient_kood)),
           ts=getdate(),
           cu='XML',
           Field57=null(z.email,(select email from kliendid where
kood=z.klient_kood)),
           objekt=null(z.objekt,(select objekt from kliendid
where kood=z.klient_kood)),
           hinnakiri=(select hinnakiri from kliendid where
kood=z.klient_kood),
           kliendi_tellimus=convert(nvarchar(max),@webid)
           from (select * from xml_in_imago_tellimused where
number=@webid)z

           where tell_tellimused.number=@number

           select @maa=maa from kliendid where kood=(select klient_kood
from xml_in_imago_tellimused where number=@number)
/*
           insert into tell_tellimused (number, myyja, aeg, klient_kood,
arvetasub, tingimus, ladu, klient_nimi, lahetusviis
           , kommentaar, valuuta, kurssbvl
           , esindaja, telefon, aadress1, aadress2, aadress3
           , lahetusaadress1, lahetusaadress2, lahetusaadress3
           , klient_nimi_lahetusel
           , ts, cu, Field57, objekt
           , hinnakiri
           )
           SELECT @number
           ,iif(isnull('myyja','')!='',myyja,iif(isnull((select myyja
from kliendid where kood=xml_in_imago_tellimused.arvetasub),'')!='',(select
myyja from kliendid where
kood=xml_in_imago_tellimused.arvetasub),iif(isnull((select myyja from
kliendid where kood=xml_in_imago_tellimused.klient_kood),'')!='',(select
myyja from kliendid where kood=xml_in_imago_tellimused.klient_kood,'XML'))))
           , aeg
           , klient_kood
           , arvetasub
           , isnull(tingimus,(select tingimus from kliendid where
kood=klient_kood))
           , isnull(ladu,'')

```

```
        , isnull(klient_nimi,(select nimi from kliendid where
kood=klient_kood))
        , isnull(tingimus,(select tingimus from kliendid where
kood=klient_kood))
        , kommenteer
        , 'EUR', 1
        , isnull(esindaja,(select kontakt from kliendid where
kood=klient_kood))
        , isnull(telefon,(select telefon from kliendid where
kood=klient_kood))
        , isnull(aadress1,(select aadress1 from kliendid where
kood=klient_kood))
        , isnull(aadress2,(select aadress2 from kliendid where
kood=klient_kood))
        , isnull(aadress3,(select aadress3 from kliendid where
kood=klient_kood))
        , isnull(lahaadress1,(select lahaadress1 from kliendid where
kood=klient_kood))
        , isnull(lahaadress2,(select lahaadress2 from kliendid where
kood=klient_kood))
        , isnull(lahaadress3,(select lahaadress3 from kliendid where
kood=klient_kood))
        , isnull(klientnimi_lahetusel,(select nimi_lahetusel from
kliendid where kood=klient_kood))

        , GETDATE(), 'XML'
        , isnull(email,(select email from kliendid where
kood=klient_kood))
        , isnull(objekt,(select objekt from kliendid where
kood=klient_kood))
        ,(select hinnakiri from kliendid where kood=klient_kood)
        FROM xml_in_imago_tellimused where number=@number
*/
    select * from in_xml_log order by rn desc
    insert into tell_tellimused_read
    (number, artikkeli, variant, konto, kogus, field8, yhikuhind,
summa, ostuhind, nimetus, kmkood, r_kommenteer, rn, rv)
    select @number, artikkeli,variant, (select myyk_eestis from
artikliklassid where kood=(select klass from artiklid where kood=artikkeli)),
kogus
    , ale
    , isnull(hind,(select baashind from artiklid where
kood=artikkeli))
    , kogus*isnull(hind,(select baashind from artiklid where
kood=artikkeli))*(100-ISNULL(ale,0))/100
    , dbo.kesk_hind(artikkeli,getdate()), nimetus
    , (select kmk_eesti from artikliklassid where kood=(select
klass from artiklid where kood=artikkeli))
    ,kommenteer, rn, rn
    FROM xml_in_imago_tellimused_read where number=@webid
```

```

        update tell_tellimused_read
        set kmkood=ISNULL((select kmkood from artiklid where
kood=tell_tellimused_read.artikkeli),(select kmk_eesti from artikliklassid
where kood=(select klass from artiklid where
kood=tell_tellimused_read.artikkeli)))
        where number=@number and kmkood is null
        UPDATE tell_tellimused_read set tkkm = dbo.summaKM
(yhikuhind,kmkood), rsum = dbo.summaKM(summa,kmkood)      where number=@number

        update tell_tellimused_read
        set konto=ISNULL((select konto_myyk from artiklid where
kood=tell_tellimused_read.artikkeli),(select myyk_eestis from artikliklassid
where kood=(select klass from artiklid where
kood=tell_tellimused_read.artikkeli)))
        where number=@number and konto is null

        EXEC dbo.tell_tellimused_renum @number
        EXEC dbo.arvuta_tellimus @number
        update tell_tellimused_read set rv=rn where number=@number
        exec hooldus_vaba 'tellimus',@number
        set @koodid=@koodid+convert(nvarchar,@number)
        insert into kliendid (kood, nimi, aadress1, aadress2, aadress3,
nimi_lahetusel, lahaadress1, lahaadress2, lahaadress3
, kontakt, email, telefon
,klient_tyyp, klass, regnr, kliendikaart
, cu, ts)
        select top 1
            klient_kood, klient_nimi, aadress1, aadress2, aadress3,
klientnimi_lahetusel, lahaadress1, lahaadress2, lahaadress3
, esindaja,email,telefon
,klient_tyyp, klient_klass, klient_regnr, klient_kliendikaart
,'XML',GETDATE()
        FROM xml_in_imago_tellimused where number=@webid
        and ISNULL(klient_kood,'')!=''
        and klient_kood not in (select kood from kliendid)
        insert into #results values (@webid, 'ORDER', 0, 'OK','Orders')
    end
    ELSE
    BEGIN
        insert into #results values (@webid, 'ORDER', 2,
'Duplicate','Orders')
    END

        set @x=@x+1
    end
    FETCH NEXT FROM tellimused INTO @webid, @appkey
    if @@FETCH_STATUS = 0 set @koodid=@koodid+'';
END
CLOSE tellimused
DEALLOCATE tellimused

```

```
--cleanup
--delete from xml_in_imago_tellimused_klient where number in (select number
from xml_in_imago_tellimused where x=@key)
delete from xml_in_imago_tellimused_read where number in (select number from
xml_in_imago_tellimused where x=@key)
delete from xml_in_imago_tellimused where x=@key

-----
-----
-
--tulemused valja

if (select COUNT(*) from #results)=0
    insert into #results values (NULL, 'GENERAL ERROR', 99, 'No processable
data found',NULL)

select @result1=
(select result as "@Type", descr as "@Desc", number as "@docid", tyyp as
"@doctype", submittype as "@submit"
 from #results for xml path ('Result'))

set @result2='<?xml version="1.0"
encoding="UTF-8"?><results>' + CONVERT(nvarchar(max),@result1) + '</results>'

select @result2
drop table #results

delete from in_xml_log where datediff(day,ts_inserted,getdate())>=5
```

From:  
<https://wiki.directo.ee/> - **Directo Help**

Permanent link:  
<https://wiki.directo.ee/lv/procedures?rev=1600180335>

Last update: **2020/09/15 17:32**