

# Table of Contents

- Deliveries (delivery)** ..... 3
  - Output (get)** ..... 3
    - Query (get) ..... 3
    - Header ..... 3
    - Rows ..... 4
  - Input (put)** ..... 4
    - Header ..... 5
    - Rows ..... 5
    - Transport parameters ..... 5
    - Response ..... 5



# Deliveries (delivery)

Deliveries. Domain: Stock.

<b>what</b>	delivery
<b>Direction</b>	Output (get), Input (put)
<b>Endpoint</b>	POST <a href="https://login.directo.ee/xmlcore/cap_xml_direct/xmlcore.asp">https://login.directo.ee/xmlcore/cap_xml_direct/xmlcore.asp</a>
<b>Schema (output)</b>	<a href="#">ws_lahetused.xsd</a>
<b>Schema (input)</b>	<a href="#">xml_IN_lahetused.xsd</a>

## Output (get)

### Query (get)

Parameter	Description
token	interface token (required)
get	1
what	delivery
number	optional filter
ordernumber	optional filter
customercode	optional filter
status	optional filter
confirmed	optional filter
stock	optional filter
ts	changed-since (for syncing)

### Header

XML field	SQL field	Type	Length	UI label	Description
number	number	int	9	Lähetuse nr	
ordernumber	number_tellimus	int	9	Tellimus nr	
date	aeg	dateTime		Lähetuse aeg	
stock	ladu	string		Ladu	length: 64
status	staatus	string	64	Staatus	
customercode	klient_kood	string	64	Kliendi kood	
customername	klient_nimi	string	510	Kliendi nimi	
delivery_type	lahetusviis	string	64	Läh. viis	
address1	aadress1	string	255	aadress, ! vastavalt seadetele	
address2	aadress2	string	200	aadress, ! vastavalt seadetele	
address3	aadress3	string	100	aadress, ! vastavalt seadetele	
comment	field24	string	510	Tekst	
country	asumaa	string	4	Sihtriik	

XML field	SQL field	Type	Length	UI label	Description
datafield1	lisa_field1	string	510	Lisaväli 1, ! vastavalt seadetele	
datafield2	lisa_field2	string	510	Lisaväli 2, ! vastavalt seadetele	
datafield3	lisa_field3	string	510	Lisaväli 3, ! vastavalt seadetele	
datafield4	lisa_field4	string	510	Lisaväli 4, ! vastavalt seadetele	
datafield5	lisa_field5	string	510	Lisaväli 5, ! vastavalt seadetele	
datafield6	lisa_field6	string	510	Lisaväli 6, ! vastavalt seadetele	
datafield7	lisa_field7	string	510	Lisaväli 7, ! vastavalt seadetele	
object	objekt	string	255	Objekt	
project	projekt	string	32	Projekt	
confirmed	kinnitatud	int	9	Suletud	closed document = 1
ts	ts	dateTime			document last changed

### Rows

XML field	SQL field	Type	Length	UI label	Description
item	artikkel	string	510	Artikkel	
qty	kogus	decimal		Lähetamisel	
description	nimetus	string	510	Nimetus	
variant	variant	string	32		
serialnumber	seerianumber	string	50	SN/Mudel	
stock	r_ladu	string	64	Ladu	
text1	tekst1	string	64		
text2	tekst2	string	64		
object	objektid	string	255	Objekt	
project	r_projekt	string	32	Projekt	
shelf	riiul	string	32	Riitul	
order	tellimus	string	9	Tellimus nr	Seotud Tellimuse number
orderrow	rn	int	9		Seotu Tellimuse rea number
rn	reanr	int	9	RN	Lähetuse rea number

### Input (put)



**Create:** send the document. **Modify:** requires xd\_update=1 and posting the **whole document**. Default values (ALT . FROM): [Mandatory fields](#).

- A **confirmed** document cannot be modified (response Type=14).

- Confirmation can be controlled via the XML field `confirm` (in addition to `xd_confirm`).

## Header

XML field	SQL field	Type	Length	Mandatory	UI label	Description
number	number	int	9	yes		document number/ID, mandatory; It must be unique for each document and remain same if more than one transaction of the same document is necessary
status	staatus	string	50		Staatus	
datafield1	lisa_field1	string	255		Lisaväli 1	
datafield2	lisa_field2	string	255		Lisaväli 2	
datafield3	lisa_field3	string	255		Lisaväli 3	
datafield4	lisa_field4	string	255		Lisaväli 4	
datafield5	lisa_field5	string	255		Lisaväli 5	
datafield6	lisa_field6	string	255		Lisaväli 6	
datafield7	lisa_field7	string	255		Lisaväli 7	
text1	tekst1	string				
text2	tekst2	string				
confirm	kinnita	int				"1" - confirm document

## Do not send:

- `session_id` - for internal use at Directo side, do not send this field!

## Rows

XML field	SQL field	Type	Length	Mandatory	UI label	Description
item	artikkel	string	32		Artikkel	
serialnumber	seerianumber	string	50		SN	
variant	variant	string	32			
qty	kogus	decimal			Kogus	
text1	tekst1	string	32			
text2	tekst2	string	32			
shelf	riiul	string	32		Riiul	
stock	r_ladu	string	255		Ladu	
rn	reanr	int			Nr	row order number in document 1 - N

## Transport parameters

Component-specific; add from the source wiki if this component has parameters.

## Response

`docid` = number of the created/updated document. Error codes: [Responses and error codes](#).

```
<results>  
  <Result Type="0" Desc="Created" docid="100001" doctype="DELIVERY"  
  submit="Deliveries"/>  
</results>
```

From:  
<https://wiki.directo.ee/> - **Directo Help**

Permanent link:  
[https://wiki.directo.ee/en/xml\\_direct/ladu/delivery](https://wiki.directo.ee/en/xml_direct/ladu/delivery)

Last update: **2026/06/25 15:24**

