

Table of Contents

Price formula rows (priceformularow)

Output (get)

Query (get)

Header

Input (put)

Header

Rows

Transport parameters

Response

3

3

3

4

4

4

5

5

Price formula rows (priceformularow)

Price formula rows. Domain: Sales.

what	priceformularow
Direction	Output (get), Input (put)
Endpoint	POST https://login.directo.ee/xmlcore/cap_xml_direct/xmlcore.asp
Schema (output)	ws_hinnavalemid.xsd
Schema (input)	xml_IN_hinnavalemid.xsd

Output (get)

Query (get)

Parameter	Description
token	interface token (required)
get	1
what	priceformularow
class	optional filter
code	optional filter
type	optional filter
barcode	optional filter
supplier	optional filter
supplieritem	optional filter
closed	optional filter
ts	changed-since (for syncing)

Header

XML field	SQL field	Type	Length	UI label	Description
code	kood	string	32	Kood	
class	klass	string	32	Klass	
item	artikkel	string	32	Artikkel	
type	mida	int	1	Mõjub	
decimalplaces	kohad	int	1	Kohta	
discount	ale	decimal		ALE	
supplier	hankija	string	32	Hankija	
project	projekt	string	32	(header)	
date1	aeg1	dateTime		Aeg1	
date2	aeg2	dateTime		Aeg2	
rounding	ymardus	decimal		Korrektsoon	
discountqty	ale_kogus	decimal		Alates kogusest	
data	data	string	32	Art.lisaväli	

XML field	SQL field	Type	Length	UI label	Description
datacontent	datasisu	string	4000	Sisu	
uuid	row_id	int			Directo unique id for editing rows
ts	ts	dateTime			document last changed

Input (put)

Attachments: **not supported**. Approvals: **not supported**. In the event of a modification, all rows must be resubmitted with the correct UUID values. To add rows, leave the UUID field blank; a new row will then be created and assigned a new UUID.



Create: send the document. Default values (ALT .FROM): [Mandatory fields](#). General modification rules: [Input principles](#).

Header

XML field	SQL field	Type	Length	Mandatory	UI label	Description
project	projekt	string	32			
code	kood	string	32	yes	Kood	document number/ID, mandatory; It must be unique for each document and remain same if more than one transaction of the same document is necessary
name	nimi	string	255		Nimi (header)	
text1	tekst1	string	255			
text2	tekst2	string	255			
currency	valuuta	string				
object	objekt	string				
order	so	int				

Do not send:

- session_id - for internal use at Directo side, do not send this field!

Rows

XML field	SQL field	Type	Length	Mandatory	UI label	Description
class	klass	string	32		Klass	
item	artikkel	string	32		Artikkel	
name	nimi	string	255		Nimi (row)	
type	mida	int	1		Mõjub	
decimalplaces	kohad	int	1		Kohta	
discount	ale	decimal			ALE	
supplier	hankija	string	32		Hankija	

XML field	SQL field	Type	Length	Mandatory	UI label	Description
data	data	string	32		Art.lisaväli	
datacontent	datasisu	string	4000		Sisu	
date1	aeg1	dateTime			Aeg1	
date2	aeg2	dateTime			Aeg2	
time1	kell1	time			Kell1	
time2	kell2	time			Kell2	
rounding	ymardus	decimal			Korrektsoon	
discountqty	ale_kogus	decimal			Alates kogusest	
recipe	retsept	string	32			
rowproject	r_projekt	string	32			
rowobject	r_objekt	string	255			
variant	variant	string	32		Variant	
rn	rn	int			Nr	row order number in document 1 - N ALT.FROM: random
uuid	row_id	int				Directo unique id for editing rows

Transport parameters

This component has no transport parameters.

Response

docid = number of the created/updated document. Error codes: [Responses and error codes](#).

```
<results>
  <Result Type="0" Desc="Created" docid="100001" doctype="PRICEFORMULAROW"
  submit="Price formula rows"/>
</results>
```

From:

<https://wiki.directo.ee/> - Directo Help

Permanent link:

https://wiki.directo.ee/en/xml_direct/muuk/priceformularow?rev=1790164721

Last update: 2026/09/23 14:58

