

# Table of Contents

- Absences (absence)** ..... 3
- Output (get)** ..... 3
- Query (get) ..... 3
- Header ..... 3
- Rows ..... 3
- Input (put)** ..... 4
- Header ..... 4
- Rows ..... 4
- Transport parameters ..... 5
- Response ..... 5



# Absences (absence)

Absences. Domain: HR.

<b>what</b>	absence
<b>Direction</b>	Output (get), Input (put)
<b>Endpoint</b>	POST <a href="https://login.directo.ee/xmlcore/cap_xml_direct/xmlcore.asp">https://login.directo.ee/xmlcore/cap_xml_direct/xmlcore.asp</a>
<b>Schema (output)</b>	<a href="#">ws_puudumised.xsd</a>
<b>Schema (input)</b>	<a href="#">xml_IN_puudumised.xsd</a>

## Output (get)

### Query (get)

Parameter	Description
token	interface token (required)
get	1
what	absence
number	optional filter
confirmed	optional filter
employee	optional filter
ts	changed-since (for syncing)

### Header

XML field	SQL field	Type	Length	UI label	Description
number	number	int			
confirmed	kinnitatus	int			
date1	aeg1	dateTime			
date2	aeg2	dateTime			
comment	selgitus	string	255		
employee	persoon	string	32		
ts	ts	dateTime			

### Rows

XML field	SQL field	Type	Length	UI label	Description
employee	persoon	string	32		
absencetype	r_liik	string	32		
date1	r_aeg1	dateTime			
date2	r_aeg2	dateTime			
comment	kommentaar	string	255		
denied	keeldus	dateTime			
deniedcomment	keeldumise_kommentaar	string			

XML field	SQL field	Type	Length	UI label	Description
inadvance	ette	int			
substitute	asendaja	string	32		
rn	rn	int			

## Input (put)



**Create:** send the document. **Modify:** requires xd\_update=1 and posting the **whole document**. Default values (ALT . FROM): [Mandatory fields](#).

- A **confirmed** document cannot be modified (response Type=14).

## Header

XML field	SQL field	Type	Length	Mandatory	UI label	Description
number	number	int	9	yes	Laekumine	document number/ID, mandatory; It must be unique for each document and remain same if more than one transaction of the same document is necessary
date1	aeg1	dateTime				
date2	aeg2	dateTime				
comment	selgitus	string	255			
employeecode	persoon	string	32			
delete	kustuta	int				„1“ means delete

### Do not send:

- session\_id - for internal use at Directo side, do not send this field!

## Rows

XML field	SQL field	Type	Length	Mandatory	UI label	Description
employeecode	persoon	string	32			
absencetype	r_liik	string	32			
date1	r_aeg1	dateTime				
date2	r_aeg2	dateTime				
newend	uus_lopp	dateTime				
comment	kommentaari	string	255			
inadvance	ette	int				
substitute	asendaja	string	32			
rn	rn	int				

## Transport parameters

Component-specific; add from the source wiki if this component has parameters.

## Response

docid = number of the created/updated document. Error codes: [Responses and error codes](#).

```
<results>
  <Result Type="0" Desc="Created" docid="100001" doctype="ABSENCE"
submit="Absences"/>
</results>
```

From:

<https://wiki.directo.ee/> - **Directo Help**

Permanent link:

[https://wiki.directo.ee/en/xml\\_direct/personal/absence](https://wiki.directo.ee/en/xml_direct/personal/absence)

Last update: **2026/06/25 15:24**

