

Sisukord

- Events (event)** 3
- Output (get)** 3
- Query (get) 3
- Header 3
- Extra fields 4
- Input (put)** 4
- Header 4
- Extra fields 6
- Source 6
- Transport parameters 6
- Response 6

Events (event)

Events. Domain: Project.

what	event
Direction	Output (get), Input (put)
Endpoint	POST https://login.directo.ee/xmlcore/cap_xml_direct/xmlcore.asp
Schema (output)	ws_syndmused.xsd
Schema (input)	xml_IN_syndmused.xsd

Output (get)

Query (get)

Parameter	Description
token	interface token (required)
get	1
what	event
code	optional filter
extid	optional filter
customercode	optional filter
type	optional filter
status	optional filter
ts	changed-since (for syncing)

Header

XML field	SQL field	Type	Length	UI label	Description
code	kood	int	9	Sündmus	
type	tyyp	string	32		UI ¦Sündmuse tüüp¦
status	status	string	32	Staatus	
startdate	aeg1	dateTime			UI ¦Algus¦
enddate	aeg2	dateTime			UI ¦Lõpp¦
eventcontacttype	k_tyyp	string	64		UI ¦Kontakti tüüp¦ KLIENT or HANKIJA (customer or supplier)
eventcontactcode	k_kood	string	32		UI ¦Kood¦
eventcontactname	k_nimi	string	255		UI ¦Nimi¦
eventcontactperson	k_kontakt	string	255		UI ¦Kontaktisik¦
phone	k_telefon	string	255		UI ¦Telefon¦
email	k_email	string	255		UI ¦Meil¦
address	k_aadress	string	255		UI ¦Aadress¦
fax	k_faks	string	64		UI ¦Faks¦
project	projekt	string	32		UI ¦Projekt¦

XML field	SQL field	Type	Length	UI label	Description
assignedby	kasutaja	string	32		UI Kasutaja
assignedto	tegija	string	32		UI Tegija
description	sisu	string	4000		or infinite (slower); UI Sündmuse kirjeldus
feedback	feedback	string	4000		or infinite (slower); UI Tagasiside
object	objekt	string	255		UI Objekt
comment	markus	string	255		UI Märkus
priceformula	hinnavalem	string	32		UI Hinnavalem
contract	leping	int			UI Leping
asset	inventar	string	32		UI Inventar
priority	prioriteet	string	32		UI Prioriteet
extid	ext_id	string	32		UI
sourcenumber	src_number	string	32		UI
sourceunit	src_unit	string	32		UI
cu	cu	string	32	Viimati muutis	document last changed by
ts	ts	dateTime			document last changed

Extra fields

XML field	SQL field	Type	Length	UI label	Description
code	kood	string	32		
content	sisu	string	2000	Sisu	
param	param	string	64	Parameeter	

Input (put)



Create: send the document. **Modify:** requires xd_update=1 and posting the **whole document**. Default values (ALT . FROM): [Mandatory fields](#).

- A **confirmed** document cannot be modified (response Type=14).

Header

XML field	SQL field	Type	Length	Mandatory	UI label	Description
ext_unique_id	ext_unique_id	string	100		! according to settings, default field is ext_id	Needed for creating new events. Transport parameter „uniqueid“ must be set up correctly and „ext_id“ field is best for that; It must be unique for each document and remain same if more than one transaction of the same document is necessary
code	kood	int	9		Sündmus	document number/ID used for updating events; It must be unique for each document and remain same if more than one transaction of the same document is necessary
type	tyyp	string	32			UI ;Sündmuse tüüp;
status	status	string	32		Staatus	
startdate	aeg1	dateTime				UI ;Algus;
enddate	aeg2	dateTime				UI ;Lõpp;
eventcontacttype	k_tyyp	string	64			UI ;Kontakti tüüp; KLIENT or HANKIJA (customer or supplier)
eventcontactcode	k_kood	string	32			UI ;Kood;
eventcontactname	k_nimi	string	255			UI ;Nimi; ALT.FROM: customer
eventcontactperson	k_kontakt	string	255			UI ;Kontaktisik; ALT.FROM: customer
phone	k_telefon	string	255			UI ;Telefon; ALT.FROM: customer
email	k_email	string	255			UI ;Meil; ALT.FROM: customer
address	k_aadress	string	255			UI ;Aadress; ALT.FROM: customer
fax	k_faks	string	64			UI ;Faks;
project	projekt	string	32			UI ;Projekt;
assignedby	kasutaja	string	32			UI ;Kasutaja;
assignedto	tegija	string	32			UI ;Tegija;

XML field	SQL field	Type	Length	Mandatory	UI label	Description
description	sisu	string	4000			or infinite (slower); UI !Sündmuse kirjeldus!
feedback	feedback	string	4000			or infinite (slower); UI !Tagasiside!
object	objekt	string	255			UI !Objekt!
comment	markus	string	255			UI !Märkus!
priceformula	hinnavalem	string	32			UI !Hinnavalem!
contract	leping	int				UI !Leping!
asset	inventar	string	32			UI !Inventar!
priority	prioriteet	string	32			UI !Prioriteet!
extid	ext_id	string	32			UI ! do not use it if ext_unique_id is already used as ext_id field !
sourceunit	src_unit	string	32			UI ! Source !
sourcenumbr	src_number	string	32			UI ! !
item	artikkel	string				
itemname	artikkel	string				

Do not send:

- session_id - for internal use at Directo side, do not send this field!

Extra fields

XML field	SQL field	Type	Length	Mandatory	UI label	Description
code	kood	string	32			
content	sisu	string	2000		Sisu	
param	param	string	64		Parameeter	

Source

XML field	SQL field	Type	Length	Mandatory	UI label	Description
sourceunit	src_unit	string	32			UI ! Source !
sourcenumbr	src_number	string	32			UI ! !

Transport parameters

Component-specific; add from the source wiki if this component has parameters.

Response

docid = number of the created/updated document. Error codes: [Responses and error codes](#).

```
<results>
  <Result Type="0" Desc="Created" docid="100001" doctype="EVENT"
```

```
submit="Events"/>  
</results>
```

From:
<https://wiki.directo.ee/> - **Directo Help**

Permanent link:
https://wiki.directo.ee/en/xml_direct/projekt/event

Last update: **2026/06/25 15:24**

