

Sisukord


```
--server DIRECT015B
USE ocra_getz_lv
GO

ALTER      PROCEDURE [dbo].[xml_core_SISSE_webshop] AS
DECLARE @klient_kood bigint, @kood bigint, @nimitmp nvarchar(255),@addrtmp
nvarchar(255),@konttmp nvarchar(255), @koodid varchar(1000)
declare @ladu nvarchar(32), @seeria nvarchar(32), @objekt nvarchar(32), @s1
int, @s2 int, @webid nvarchar(32), @webtype nvarchar(32)
declare @number int, @maa int, @kmk nvarchar(32), @x int, @kinnitatus int
DECLARE @myyja nvarchar(32), @aeg datetime
declare @key nvarchar(32), @appkey nvarchar(64), @appkey_setting
nvarchar(64)
declare @result1 xml, @result2 nvarchar(max)
declare @artikkel nvarchar(32), @id_exist int
declare @kl_kood nvarchar(32), @nimi nvarchar(255), @kustuta int
declare @ag datetime
declare @err nvarchar(32)
select @ag =getdate()
set @key=CONVERT(nvarchar,getdate())
update in_webshop_tell_tellimused set x=@key where x is null
update xml_in_imago_tellimused set x=@key where x is null
set @koodid=''

select @appkey_setting=setting from settings where ID='xmlcore_key'

create table #results
(number nvarchar(32), tyyp nvarchar(32), result int, descr nvarchar(255),
submittype nvarchar(32))

--vastuvotmine, kogused
--SELECT * FROM in_webshop_tell_tellimused WHERE number = '2000117'
-- DELETE FROM in_webshop_tell_tellimused WHERE number = '2000117'
-- UPDATE in_webshop_tell_tellimused SET x = null WHERE number = '2000117'
-- EXEC [dbo].[xml_core_SISSE_webshop]

--sales order from E-agent [LV software]
declare tellimused cursor for select number, appkey from
in_webshop_tell_tellimused with(nolock) where x=@key
open tellimused
FETCH NEXT FROM tellimused INTO @webid, @appkey
WHILE @@FETCH_STATUS = 0
BEGIN
    if ISNULL(@appkey,'')!=ISNULL(@appkey_setting,'')
    begin
        insert into #results values (@appkey, 'ORDER', 1, 'Incorrect
key','Orders')
```

```
end
else
begin

    select @id_exist=count(*) from tell_tellimused with(nolock) where
number=@webid
    if @id_exist=0
    BEGIN
        set @number=@webid
        select @maa=maa from kliendid with(nolock) where kood=(select
klient_kood from in_webshop_tell_tellimused with(nolock) where
number=@number)

        insert into tell_tellimused (number, myyja, aeg, klient_kood,
arvetasub, tingimus, ladu, klient_nimi, lahetusviis
        , kommentaar, valuuta, kurssbv1
        ,esindaja, telefon, address1, address2, address3
        ,lahetusaadress1, lahetusaadress2, lahetusaadress3
        ,klient_nimi_lahetusel
        , ts, cu, Field57, objekt
        ,hinnakiri, lahetusaeg, lisa_field1
        )
        SELECT @number
        ,ISNULL(myyja, 'XML')
        , aeg
        , klient_kood
        , isnull((select top 1 arvetasub from kliendid where
kood=klient_kood),arvetasub)
        , isnull(tingimus,(select TOP 1 tingimus from kliendid
with(nolock) where kood=klient_kood))
        , isnull(ladu,'GAL')
        , isnull(klient_nimi,(select TOP 1 nimi from kliendid
with(nolock) where kood=klient_kood))
        , isnull(tingimus,(select TOP 1 tingimus from kliendid
with(nolock) where kood=klient_kood))
        ,kommentaar
        , 'EUR', 1
        , isnull(esindaja,(select TOP 1 kontakt from kliendid
with(nolock) where kood=klient_kood))
        , isnull(telefon,(select TOP 1 telefon from kliendid
with(nolock) where kood=klient_kood))
        , isnull(address1,(select TOP 1 address1 from kliendid
with(nolock) where kood=klient_kood))
        , isnull(address2,(select TOP 1 address2 from kliendid
with(nolock) where kood=klient_kood))
        , isnull(address3,(select TOP 1 address3 from kliendid
with(nolock) where kood=klient_kood))
        , isnull(lahaaddress1,(select TOP 1 lahaaddress1 from kliendid
with(nolock) where kood=klient_kood))
        , isnull(lahaaddress2,(select TOP 1 lahaaddress2 from kliendid
with(nolock) where kood=klient_kood))
```

```

        , isnull(lahaaddress3,(select TOP 1 lahaaddress3 from kliendid
with(nolock) where kood=klient_kood))
        , isnull(klientnimi_lahetusel,(select TOP 1 nimi_lahetusel
from kliendid v where kood=klient_kood))

        , GETDATE(), 'XML'
        , isnull(email,(select TOP 1 email from kliendid
with(nolock) where kood=klient_kood))
        , isnull(objekt,(select TOP 1 objekt from kliendid
with(nolock) where kood=klient_kood))
        ,(select TOP 1 hinnakiri from kliendid with(nolock) where
kood=klient_kood)
        , lahetusaeg
        , isnull(lisa_field1,(select TOP 1 sisu from yld_data
with(nolock) where kood='TRANSPORTER' AND KLASS='KLIENT' AND
kaart=klient_kood))
        FROM in_webshop_tell_tellimused with(nolock) where
number=@number

-- UPDATE in_tell_tellimused_read SET artikkel = ISNULL((select
artikkel from artiklid_hankija_artiklid with(nolock) where hankija_artikkel
= in_tell_tellimused_read.artikkel),artikkel) WHERE NOT EXISTS(SELECT top 1
kood FROM artiklid WITH(nolock) WHERE kood =
in_tell_tellimused_read.artikkel)

        insert into tell_tellimused_read
        (number,yhik, artikkel, variant, konto, kogus, field8,
yhikuhind, summa, ostuhind, nimetus, kmkood, r_kommentaar, rn, rv)
        select @number
        ,isnull((select top 1 yhik from artiklid where
kood=artikkel),'gb')
        , artikkel
        ,variant
        , isnull((select konto_myyk from artiklid where
kood=in_webshop_tell_tellimused_read.artikkel),(select TOP 1 myyk_eestis
from artikliklassid with(nolock) where kood=(select TOP 1 klass from
artiklid where kood=artikkel)))
        , kogus
        , case
            when EXISTS (select top 1 ale from mr_hinnavalemid_read
with(nolock) where mida='8' and kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number) and ((select aeg from
tell_tellimused with(nolock) where number=@number) between aeg1 and aeg2 )
and in_webshop_tell_tellimused_read.artikkel=artikkel or mida='8' and
kood=(select top 1 hinnakiri from tell_tellimused with(nolock) where
number=@number) and(aeg1 is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkel=artikkel)
            then
                ('0')

        when ((select top 1 ale from mr_hinnavalemid_read where

```

```

mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 )) is NOT null
    then (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 ))

when ((select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and AEG1 IS NULL AND AEG2 IS NULL) is NOT null)
    then (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) AND aeg1 IS NULL and aeg2 IS NULL )

    --when ((select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 )) is null
        --and (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and (aeg1 is NOT null and aeg2 is NOT null ) AND
((select top 1 AEG from tell_tellimused with(nolock) where number=@number)
between AEG1 AND AEG2)) is not null)
        --then (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and (aeg1 is NOT null and aeg2 is NOT null ) AND
((select top 1 AEG from tell_tellimused with(nolock) where number=@number)
between AEG1 AND AEG2))
            when
                ((select top 1 ale from mr_hinnavalemid_read
                    inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
                    inner join tell_tellimused ON
tell_tellimused.number=@number
                    where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
                    and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
                    and
                    ((tell_tellimused.aeg) between mr_hinnavalemid_read.aeg1
and mr_hinnavalemid_read.aeg2 )) is not null)
                    then (select top 1 ale from mr_hinnavalemid_read
                        inner join artiklid ON

```

```
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
    inner join tell_tellimused ON
tell_tellimused.number=@number
    where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
    and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
    and
    ((tell_tellimused.aeg) between mr_hinnavalemid_read.aeg1
and mr_hinnavalemid_read.aeg2 ))
    when ((select top 1 ale from mr_hinnavalemid_read
    inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
    inner join tell_tellimused ON
tell_tellimused.number=@number
    where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
    and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
    and
    ((tell_tellimused.aeg) between mr_hinnavalemid_read.aeg1
and mr_hinnavalemid_read.aeg2 )) is null and (select top 1 ale from
mr_hinnavalemid_read
    inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
    inner join tell_tellimused ON
tell_tellimused.number=@number
    where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
    and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
    and
    (mr_hinnavalemid_read.aeg1 is null and
mr_hinnavalemid_read.aeg2 is null )) is not null)
    then (select top 1 ale from mr_hinnavalemid_read
    inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
    inner join tell_tellimused ON
tell_tellimused.number=@number
    where mr_hinnavalemid_read.klass=artiklid.klass and
mida='0'
    and mr_hinnavalemid_read.kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
    and
    (mr_hinnavalemid_read.aeg1 is null and
mr_hinnavalemid_read.aeg2 is null )) END
    -- when
    -- ((select top 1 ale from mr_hinnavalemid_read
    -- inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
    -- where mr_hinnavalemid_read.klass=artiklid.klass
```

```

--      and
--      ((select aeg from tell_tellimused with(nolock) where
number=@number) between aeg1 and aeg2)) is null and (select top 1 ale from
mr_hinnavalemid_read inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel where
mr_hinnavalemid_read.klass=artiklid.klass and (aeg1 is null and aeg2 is
null)) is not null)
--      then (select top 1 ale from mr_hinnavalemid_read inner
join artiklid ON artiklid.kood=in_webshop_tell_tellimused_read.artikkel
where mr_hinnavalemid_read.klass=artiklid.klass and (aeg1 is null and aeg2
is null))END
-- ,case when EXISTS (select top 1 ale from mr_hinnavalemid_read
with(nolock) where mida='8' and kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number) and ((select aeg from
tell_tellimused with(nolock) where number=@number) between aeg1 and aeg2 )
and in_webshop_tell_tellimused_read.artikkel=artikkel or mida='8' and
kood=(select top 1 hinnakiri from tell_tellimused with(nolock) where
number=@number) and(aeg1 is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkel=artikkel)
-- then
-- '0'
-- ELSE

-- isnull((select top 1 ale from mr_hinnavalemid_read with(nolock) where
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 ) and
in_webshop_tell_tellimused_read.artikkel=artikkel or mida='0' and
kood=(select top 1 hinnakiri from tell_tellimused with(nolock) where
number=@number) and(aeg1 is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkel=artikkel),
-- isnull((select top 1 ale from mr_hinnavalemid_read with(nolock)
where mida='0' and kood=(select top 1 hinnakiri from tell_tellimused
with(nolock) where number=@number) and ((select aeg from tell_tellimused
with(nolock) where number=@number) between aeg1 and aeg2 ) and klass=(select
top 1 klass from artiklid where
kood=in_webshop_tell_tellimused_read.artikkel)),(select top 1 ale from
mr_hinnavalemid_read with(nolock) where mida='0' and kood=(select top 1
hinnakiri from tell_tellimused with(nolock) where number=@number) and(aeg1
is null and aeg2 is null) and klass=(select top 1 klass from artiklid where
kood=in_webshop_tell_tellimused_read.artikkel))))
-- END

-- , isnull((select top 1 ale from mr_hinnavalemid_read
where mida='8' and artikkel=(select top 1 artikkel from
in_webshop_tell_tellimused_read where
in_webshop_tell_tellimused_read.artikkel=artikkel) and (((select aeg from
tell_tellimused where number=@number) between aeg1 and aeg2 ) or (aeg1 is
null and aeg2 is null)) and kood=(select hinnakiri from tell_tellimused
where number=@number)), 0)
-- , isnull(hind,(select dbo.get_hind6(artikkel,(SELECT top
1 hinnakiri from tell_tellimused INNER JOIN mr_hinnavalemid_read ON

```

```

mr_hinnavalemid_read.artikkel=artikkel and mida='8' and (((select aeg from
tell_tellimused where number=@number) between aeg1 and aeg2 ) or (aeg1 is
null and aeg2 is null)) where number=@number), null, null, null,null,
null,null, null, null,null,0)))
        ,case when EXISTS (select top 1 ale from
mr_hinnavalemid_read with(nolock) where mida='8'
                        and kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number)
                        and ((select aeg from tell_tellimused
with(nolock) where number=@number) between aeg1 and aeg2 )
                        and
in_webshop_tell_tellimused_read.artikkel=artikkel
                        or mida='8' and kood=(select top 1
hinnakiri from tell_tellimused with(nolock) where number=@number) and(aeg1
is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkel=artikkel)
        then
                (select dbo.get_hind6(artikkel,(SELECT top 1 hinnakiri
from tell_tellimused where number=@number), null, null ,null,null,
null,null, (select top 1 aeg from tell_tellimused where number=@number),
null,null,0))

ELSE

(select top 1 baashind from artiklid where
kood=in_webshop_tell_tellimused_read.artikkel)
        END
        , kogus*isnull(hind,(select top 1 baashind from artiklid
with(nolock) where kood=artikkel))*(100-ISNULL(ale,0))/100
        , dbo.kesk_hind(artikkel,getdate())
        , isnull(nimetus,(select top 1 nimi from artiklid
with(nolock) where kood=artikkel))
        , isnull((select top 1 kmkood from artiklid with(nolock)
where kood=artikkel),(select top 1 kmk_eesti from artikliklassid
with(nolock) where kood=(select TOP 1 klass from artiklid where
kood=artikkel)))
        ,kommentaar, ROW_NUMBER() OVER(ORDER BY rn) , ROW_NUMBER()
OVER(ORDER BY rn )
        FROM in_webshop_tell_tellimused_read with(nolock) where
number=@number

        update tell_tellimused_read
        set kmkood=ISNULL((select top 1 KMkood from artiklid
with(nolock) where kood=tell_tellimused_read.artikkel),(select kmk_eesti
from artikliklassid with(nolock) where kood=(select top 1 klass from
artiklid with(nolock) where kood=tell_tellimused_read.artikkel))
        where number=@number and kmkood is null
        UPDATE tell_tellimused_read set tkkm = dbo.summaKM
(yhikuhind,kmkood), rsum = dbo.summaKM(summa,kmkood)      where number=@number

        update tell_tellimused_read

```

```

        set konto=ISNULL((select top 1 konto_myyk from artiklid
with(nolock) where kood=tell_tellimused_read.artikkel),(select myyk_eestis
from artikliklassid with(nolock) where kood=(select top 1 klass from
artiklid with(nolock) where kood=tell_tellimused_read.artikkel))
        where number=@number and konto is null

        --EXEC dbo.tell_tellimused_renum @number
EXEC dbo.arvuta_tellimus @number
update tell_tellimused_read set rv=rn where number=@number
exec hooldus_vaba 'tellimus',@number
set @koodid=@koodid+convert(nvarchar,@number)
insert into kliendid (kood, nimi, address1, address2, address3,
nimi_lahetusel, lahaaddress1, lahaaddress2, lahaaddress3
, kontakt, email, telefon
, klient_tyyp, klass, regnr, kliendikaart
, cu, ts)
select top 1
klient_kood, klient_nimi, address1, address2, address3,
klientnimi_lahetusel, lahaaddress1, lahaaddress2, lahaaddress3
, esindaja, email, telefon
, klient_tyyp, klient_klass, klient_regnr, klient_kliendikaart
, 'XML', GETDATE()
        FROM in_webshop_tell_tellimused with(nolock) where
number=@number
        and ISNULL(klient_kood, '') != ''
        and klient_kood not in (select kood from kliendid with(nolock))
insert into #results values (@webid, 'ORDER', 0, 'OK', 'Orders')
end
ELSE
BEGIN
insert into #results values (@webid, 'ORDER', 2,
'Duplicate', 'Orders')
END

        set @x=@x+1
end
FETCH NEXT FROM tellimused INTO @webid, @appkey
if @@FETCH_STATUS = 0 set @koodid=@koodid+';'
END
CLOSE tellimused
DEALLOCATE tellimused

--cleanup
--delete from in_webshop_tell_tellimused_klient where number in (select
number from in_webshop_tell_tellimused where x=@key)

delete from in_webshop_tell_tellimused_read where number in (select number
from in_webshop_tell_tellimused where x=@key)
delete from in_webshop_tell_tellimused where x=@key

```

```
-----  
-----  
-----  
--sales orders from imago [EE software]  
  
--vastuvotmine, kogused  
declare tellimused cursor for select number, appkey from  
xml_in_imago_tellimused where x=@key  
open tellimused  
FETCH NEXT FROM tellimused INTO @webid, @appkey  
WHILE @@FETCH_STATUS = 0  
BEGIN  
    if ISNULL(@appkey, '') != ISNULL(@appkey_setting, '')  
    begin  
        insert into #results values (@appkey, 'ORDER', 1, 'Incorrect  
key', 'Orders')  
  
    end  
    else  
    begin  
        select @id_exist=count(*) from tell_tellimused where  
kliendi_tellimus=convert(nvarchar(max),@webid)  
        if @id_exist=0  
        BEGIN  
            --set @number=@webid  
            EXEC dbo.get_dok_number @moodul='tellimus',@seeria='DOC',@NUMBER  
= NULL, @cu='xmlcore', @aeg=@ag, @keel = 'default', @num =@number OUTPUT,  
@err = @err OUTPUT  
  
            update tell_tellimused set  
myyja=iif(isnull(z.myyja, '') != '', z.myyja, iif(isnull((select myyja from  
kliendid where kood=z.arvetasub), '') != '', (select myyja from kliendid where  
kood=z.arvetasub), iif(isnull((select myyja from kliendid where  
kood=z.klient_kood), '') != '', (select myyja from kliendid where  
kood=z.klient_kood), 'XML'))),  
                aeg=z.aeg,  
                klient_kood=z.klient_kood,  
                arvetasub=z.arvetasub,  
                tingimus=isnull(z.tingimus, (select tingimus from  
kliendid where kood=z.klient_kood)),  
                ladu=isnull(z.ladu, 'GAL'),  
                klient_nimi=isnull(z.klient_nimi, (select nimi from  
kliendid where kood=z.klient_kood)),  
                lahetusviis=isnull(z.tingimus, (select tingimus from  
kliendid where kood=z.klient_kood)),  
                kommentaar=z.kommentaar,  
                valuuta='EUR',  
                kurssbv1=1,  
                esindaja=isnull(z.esindaja, (select kontakt from kliendid  
where kood=z.klient_kood)),
```

```

        telefon=isnull(z.telefon,(select telefon from kliendid
where kood=z.klient_kood)),
        aadress1=isnull(z.aadress1,(select aadress1 from
kliendid where kood=z.klient_kood)),
        aadress2=isnull(z.aadress2,(select aadress2 from
kliendid where kood=z.klient_kood)),
        aadress3=isnull(z.aadress3,(select aadress3 from
kliendid where kood=z.klient_kood)),
        lahetusaadress1=isnull(z.lahaadress1,(select lahaadress1
from kliendid where kood=z.klient_kood)),
        lahetusaadress2=isnull(z.lahaadress2,(select lahaadress2
from kliendid where kood=z.klient_kood)),
        lahetusaadress3=isnull(z.lahaadress3,(select lahaadress3
from kliendid where kood=z.klient_kood)),
        klient_nimi_lahetusel=isnull(z.klientnimi_lahetusel,(select nimi_lahetusel
from kliendid where kood=z.klient_kood)),
        ts=getdate(),
        cu='XML',
        Field57=isnull(z.email,(select email from kliendid where
kood=z.klient_kood)),
        objekt=isnull(z.objekt,(select objekt from kliendid
where kood=z.klient_kood)),
        hinnakiri=(select hinnakiri from kliendid where
kood=z.klient_kood),
        kliendi_tellimus=convert(nvarchar(max),@webid)
        from (select * from xml_in_imago_tellimused where
number=@webid)z

        where tell_tellimused.number=@number

        select @maa=maa from kliendid where kood=(select klient_kood
from xml_in_imago_tellimused where number=@number)
/*
        insert into tell_tellimused (number, myyja, aeg, klient_kood,
arvetasub, tingimus, ladu, klient_nimi, lahetusviis
        , kommentaar, valuuta, kurssbv1
        ,esindaja, telefon, aadress1, aadress2, aadress3
        ,lahetusaadress1, lahetusaadress2, lahetusaadress3
        ,klient_nimi_lahetusel
        , ts, cu, Field57, objekt
        ,hinnakiri
        )
        SELECT @number
        ,iif(isnull('myyja','')!='',myyja,iif(isnull((select myyja
from kliendid where kood=xml_in_imago_tellimused.arvetasub),'')!='',(select
myyja from kliendid where
kood=xml_in_imago_tellimused.arvetasub),iif(isnull((select myyja from
kliendid where kood=xml_in_imago_tellimused.klient_kood),'')!='',(select
myyja from kliendid where kood=xml_in_imago_tellimused.klient_kood),'XML'))
        , aeg

```

```

        , klient_kood
        , arvetasub
        , isnull(tingimus,(select tingimus from kliendid where
kood=klient_kood))
        , isnull(ladu,'')
        , isnull(klient_nimi,(select nimi from kliendid where
kood=klient_kood))
        , isnull(tingimus,(select tingimus from kliendid where
kood=klient_kood))
        , kommentaar
        , 'EUR', 1
        , isnull(esindaja,(select kontakt from kliendid where
kood=klient_kood))
        , isnull(telefon,(select telefon from kliendid where
kood=klient_kood))
        , isnull(aadress1,(select aadress1 from kliendid where
kood=klient_kood))
        , isnull(aadress2,(select aadress2 from kliendid where
kood=klient_kood))
        , isnull(aadress3,(select aadress3 from kliendid where
kood=klient_kood))
        , isnull(lahaadress1,(select lahaadress1 from kliendid where
kood=klient_kood))
        , isnull(lahaadress2,(select lahaadress2 from kliendid where
kood=klient_kood))
        , isnull(lahaadress3,(select lahaadress3 from kliendid where
kood=klient_kood))
        , isnull(klientnimi_lahetusel,(select nimi_lahetusel from
kliendid where kood=klient_kood))

        , GETDATE(), 'XML'
        , isnull(email,(select email from kliendid where
kood=klient_kood))
        , isnull(objekt,(select objekt from kliendid where
kood=klient_kood))
        ,(select hinnakiri from kliendid where kood=klient_kood)
        FROM xml_in_imago_tellimused where number=@number
*/

        select * from in_xml_log order by rn desc
        insert into tell_tellimused_read
        (number, artikkel, variant, konto, kogus, field8, yhikuhind,
summa, ostuhind, nimetus, kmkood, r_kommentaar, rn, rv)
        select @number, artikkel,variant, (select myyk_eestis from
artikliklassid where kood=(select klass from artiklid where kood=artikkel)),
kogus
        , ale
        , isnull(hind,(select baashind from artiklid where
kood=artikkel))
        , kogus*isnull(hind,(select baashind from artiklid where
kood=artikkel))*(100-ISNULL(ale,0))/100
        , dbo.kesk_hind(artikkel,getdate()), nimetus

```

```

        , (select kmk_eesti from artikliklassid where kood=(select
klass from artiklid where kood=artikkel))
        ,kommentaar, rn, rn
        FROM xml_in_imago_tellimused_read where number=@webid

        update tell_tellimused_read
        set kmkood=ISNULL((select kmkood from artiklid where
kood=tell_tellimused_read.artikkel),(select kmk_eesti from artikliklassid
where kood=(select klass from artiklid where
kood=tell_tellimused_read.artikkel)))
        where number=@number and kmkood is null
        UPDATE tell_tellimused_read set tkkm = dbo.summaKM
(yhikuhind,kmkood), rsum = dbo.summaKM(summa,kmkood) where number=@number

        update tell_tellimused_read
        set konto=ISNULL((select konto_myyk from artiklid where
kood=tell_tellimused_read.artikkel),(select myyk_eestis from artikliklassid
where kood=(select klass from artiklid where
kood=tell_tellimused_read.artikkel)))
        where number=@number and konto is null

        EXEC dbo.tell_tellimused_renum @number
        EXEC dbo.arvuta_tellimus @number
        update tell_tellimused_read set rv=rn where number=@number
        exec hooldus_vaba 'tellimus',@number
        set @koodid=@koodid+convert(nvarchar,@number)
        insert into kliendid (kood, nimi, aadress1, aadress2, aadress3,
nimi_lahetusel, lahaadress1, lahaadress2, lahaadress3
        , kontakt, email, telefon
        ,klient_tyyp, klass, regnr, kliendikaart
        ,cu,ts)
        select top 1
        klient_kood, klient_nimi, aadress1, aadress2, aadress3,
klientnimi_lahetusel, lahaadress1, lahaadress2, lahaadress3
        , esindaja,email,telefon
        ,klient_tyyp, klient_klass, klient_regnr, klient_kliendikaart
        ,'XML',GETDATE()
        FROM xml_in_imago_tellimused where number=@webid
        and ISNULL(klient_kood,'')!=''
        and klient_kood not in (select kood from kliendid)
        insert into #results values (@webid, 'ORDER', 0, 'OK','Orders')
    end
    ELSE
    BEGIN
        insert into #results values (@webid, 'ORDER', 2,
'Duplicate','Orders')
    END

    set @x=@x+1
end

```

```
    FETCH NEXT FROM tellimused INTO @webid, @appkey
    if @@FETCH_STATUS = 0 set @koodid=@koodid+';'
END
CLOSE tellimused
DEALLOCATE tellimused

--cleanup
--delete from xml_in_imago_tellimused_klient where number in (select number
from xml_in_imago_tellimused where x=@key)
delete from xml_in_imago_tellimused_read where number in (select number from
xml_in_imago_tellimused where x=@key)
delete from xml_in_imago_tellimused where x=@key

-----
-----
-
--tulemused valja

if (select COUNT(*) from #results)=0
    insert into #results values (NULL, 'GENERAL ERROR', 99, 'No processable
data found',NULL)

select @result1=
(select result as "@Type", descr as "@Desc", number as "@docid", ttyp as
"@doctype", submittype as "@submit"
from #results for xml path ('Result'))

set @result2='<?xml version="1.0"
encoding="UTF-8"?><results>'+CONVERT(nvarchar(max),@result1)+'</results>'

select @result2
drop table #results

delete from in_xml_log where datediff(day,ts_inserted,getdate())>=5
```

From:

<https://wiki.directo.ee/> - **Directo Help**

Permanent link:

<https://wiki.directo.ee/lv/procedures?rev=1600180324>

Last update: **2020/09/15 17:32**

