

Table of Contents


```

ALTER      PROCEDURE [dbo].[xml_core_SISSE_webshop] AS
DECLARE @klient_kood BIGINT, @kood BIGINT, @nimitmp nvarchar(255),@addrtmp
nvarchar(255),@konttmp nvarchar(255), @koodid VARCHAR(1000)
DECLARE @ladu nvarchar(32), @seeria nvarchar(32), @objekt nvarchar(32), @s1
INT, @s2 INT, @webid nvarchar(32), @webtype nvarchar(32)
DECLARE @NUMBER INT, @maa INT, @kmk nvarchar(32), @x INT, @kinnitatus INT
DECLARE @myyja nvarchar(32), @aeg datetime
DECLARE @KEY nvarchar(32), @appkey nvarchar(64), @appkey_setting
nvarchar(64)
DECLARE @result1 xml, @result2 nvarchar(MAX)
DECLARE @artikkel nvarchar(32), @id_exist INT
DECLARE @kl_kood nvarchar(32), @nimi nvarchar(255), @kustuta INT
DECLARE @ag datetime
DECLARE @err nvarchar(32)
SELECT @ag =getdate()
SET @KEY=CONVERT(nvarchar,getdate())
UPDATE in_webshop_tell_tellimused SET x=@KEY WHERE x IS NULL
UPDATE xml_in_imago_tellimused SET x=@KEY WHERE x IS NULL
SET @koodid=''

SELECT @appkey_setting=setting FROM settings WHERE ID='xmlcore_key'

CREATE TABLE #results
(NUMBER nvarchar(32), tyyp nvarchar(32), RESULT INT, descr nvarchar(255),
submittype nvarchar(32))

--vastuvotmine, kogused
--SELECT * FROM in_webshop_tell_tellimused WHERE number = '2000117'
-- DELETE FROM in_webshop_tell_tellimused WHERE number = '2000117'
-- UPDATE in_webshop_tell_tellimused SET x = null WHERE number = '2000117'
-- EXEC [dbo].[xml_core_SISSE_webshop]

--sales order from E-agent [LV software]
DECLARE tellimused cursor FOR SELECT NUMBER, appkey FROM
in_webshop_tell_tellimused WITH(nolock) WHERE x=@KEY
OPEN tellimused
FETCH NEXT FROM tellimused INTO @webid, @appkey
WHILE @@FETCH_STATUS = 0
BEGIN
    IF ISNULL(@appkey, '')!=ISNULL(@appkey_setting, '')
    BEGIN
        INSERT INTO #results VALUES (@appkey, 'ORDER', 1, 'Incorrect
key', 'Orders')

    END

    ELSE
    BEGIN

```

```

SELECT @id_exist=COUNT(*) FROM tell_tellimused WITH(nolock) WHERE
NUMBER=@webid
IF @id_exist=0
BEGIN
    SET @NUMBER=@webid

    SELECT @maa=maa FROM kliendid WITH(nolock) WHERE kood=(SELECT
klient_kood FROM in_webshop_tell_tellimused WITH(nolock) WHERE
NUMBER=@NUMBER)

    INSERT INTO tell_tellimused (NUMBER, myyja, aeg, klient_kood,
arvetasub, tingimus, ladu, klient_nimi, lahetusviis
    , kommentaar, valuuta, kurssbv1
    , esindaja, telefon, aadress1, aadress2, aadress3
    , lahetusaadress1, lahetusaadress2, lahetusaadress3
    , klient_nimi_lahetusel
    , ts, cu, Field57, objekt
    , hinnakiri, lahetusaeg, lisa_field1
    )
    SELECT @NUMBER

    , ISNULL(myyja, 'XML')
    , aeg
    , klient_kood
    , isnull((SELECT top 1 arvetasub FROM kliendid WHERE
kood=klient_kood), arvetasub)
    , isnull(tingimus, (SELECT TOP 1 tingimus FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(ladu, 'GAL')
    , isnull(klient_nimi, (SELECT TOP 1 nimi FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(tingimus, (SELECT TOP 1 tingimus FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , kommentaar
    , 'EUR', 1
    , isnull(esindaja, (SELECT TOP 1 kontakt FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(telefon, (SELECT TOP 1 telefon FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(aadress1, (SELECT TOP 1 aadress1 FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(aadress2, (SELECT TOP 1 aadress2 FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(aadress3, (SELECT TOP 1 aadress3 FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(lahaadress1, (SELECT TOP 1 lahaadress1 FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(lahaadress2, (SELECT TOP 1 lahaadress2 FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
    , isnull(lahaadress3, (SELECT TOP 1 lahaadress3 FROM kliendid
WITH(nolock) WHERE kood=klient_kood))

```

```

        , isnull(klientnimi_lahetusel,(SELECT TOP 1 nimi_lahetusel
FROM kliendid v WHERE kood=klient_kood))

        , GETDATE(), 'XML'
        , isnull(email,(SELECT TOP 1 email FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
        , isnull(objekt,(SELECT TOP 1 objekt FROM kliendid
WITH(nolock) WHERE kood=klient_kood))
        ,(SELECT TOP 1 hinnakiri FROM kliendid WITH(nolock) WHERE
kood=klient_kood)
        , lahetusaeg
        , isnull(lisa_field1,(SELECT TOP 1 sisu FROM yld_data
WITH(nolock) WHERE kood='TRANSPORTER' AND KLASS='KLIENT' AND
kaart=klient_kood))
        FROM in_webshop_tell_tellimused WITH(nolock) WHERE
NUMBER=@NUMBER

-- UPDATE in_tell_tellimused_read SET artikkel = ISNULL((select
artikkel from artiklid_hankija_artiklid with(nolock) where hankija_artikkel
= in_tell_tellimused_read.artikkel),artikkel) WHERE NOT EXISTS(SELECT top 1
kood FROM artiklid WITH(nolock) WHERE kood =
in_tell_tellimused_read.artikkel)

        INSERT INTO tell_tellimused_read
        (NUMBER,yhik, artikkel, variant, konto, kogus, field8,
yhikuhind, summa, ostuhind, nimetus, kmkood, r_kommentaar, rn, rv)
        SELECT @NUMBER
        ,isnull((SELECT top 1 yhik FROM artiklid WHERE
kood=artikkel),'gb')
        , artikkel
        ,variant
        , isnull((SELECT konto_myyk FROM artiklid WHERE
kood=in_webshop_tell_tellimused_read.artikkel),(SELECT TOP 1 myyk_eestis
FROM artikliklassid WITH(nolock) WHERE kood=(SELECT TOP 1 klass FROM
artiklid WHERE kood=artikkel)))
        , kogus
        , CASE
            WHEN EXISTS (SELECT top 1 ale FROM mr_hinnavalemid_read
WITH(nolock) WHERE mida='8' AND kood=(SELECT top 1 hinnakiri FROM
tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER) AND ((SELECT aeg FROM
tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER) BETWEEN aeg1 AND aeg2 )
AND in_webshop_tell_tellimused_read.artikkel=artikkel OR mida='8' AND
kood=(SELECT top 1 hinnakiri FROM tell_tellimused WITH(nolock) WHERE
NUMBER=@NUMBER) AND(aeg1 IS NULL AND aeg2 IS NULL) AND
in_webshop_tell_tellimused_read.artikkel=artikkel)
            THEN
                ('0')

            WHEN ((SELECT top 1 ale FROM mr_hinnavalemid_read WHERE
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel AND
mida='0' AND kood=(SELECT top 1 hinnakiri FROM tell_tellimused WITH(nolock)

```

```

WHERE NUMBER=@NUMBER) AND ((SELECT aeg FROM tell_tellimused WITH(nolock)
WHERE NUMBER=@NUMBER) BETWEEN aeg1 AND aeg2 )) IS NOT NULL)

    THEN (SELECT top 1 ale FROM mr_hinnavalemid_read WHERE
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel AND
mida='0' AND kood=(SELECT top 1 hinnakiri FROM tell_tellimused WITH(nolock)
WHERE NUMBER=@NUMBER) AND ((SELECT aeg FROM tell_tellimused WITH(nolock)
WHERE NUMBER=@NUMBER) BETWEEN aeg1 AND aeg2 ))

WHEN ((SELECT top 1 ale FROM mr_hinnavalemid_read WHERE
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel AND
mida='0' AND kood=(SELECT top 1 hinnakiri FROM tell_tellimused WITH(nolock)
WHERE NUMBER=@NUMBER) AND AEG1 IS NULL AND AEG2 IS NULL) IS NOT NULL)

    THEN (SELECT top 1 ale FROM mr_hinnavalemid_read WHERE
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel AND
mida='0' AND kood=(SELECT top 1 hinnakiri FROM tell_tellimused WITH(nolock)
WHERE NUMBER=@NUMBER) AND aeg1 IS NULL AND aeg2 IS NULL )

    --when ((select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 )) is null
    --and (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and (aeg1 is NOT null and aeg2 is NOT null ) AND
((select top 1 AEG from tell_tellimused with(nolock) where number=@number)
between AEG1 AND AEG2)) is not null)

    --then (select top 1 ale from mr_hinnavalemid_read where
mr_hinnavalemid_read.artikkel =in_webshop_tell_tellimused_read.artikkel and
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and (aeg1 is NOT null and aeg2 is NOT null ) AND
((select top 1 AEG from tell_tellimused with(nolock) where number=@number)
between AEG1 AND AEG2))

    WHEN
        ((SELECT top 1 ale FROM mr_hinnavalemid_read
INNER JOIN artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
INNER JOIN tell_tellimused ON
tell_tellimused.number=@NUMBER
WHERE mr_hinnavalemid_read.klass=artiklid.klass AND
mida='0'
AND mr_hinnavalemid_read.kood=(SELECT top 1 hinnakiri FROM
tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER)
AND
((tell_tellimused.aeg) BETWEEN mr_hinnavalemid_read.aeg1
AND mr_hinnavalemid_read.aeg2 )) IS NOT NULL)

```

```

                THEN (SELECT top 1 ale FROM mr_hinnavalemid_read
                INNER JOIN artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
                INNER JOIN tell_tellimused ON
tell_tellimused.number=@NUMBER
                WHERE mr_hinnavalemid_read.klass=artiklid.klass AND
mida='0'
                AND mr_hinnavalemid_read.kood=(SELECT top 1 hinnakiri FROM
tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER)
                AND
                ((tell_tellimused.aeg) BETWEEN mr_hinnavalemid_read.aeg1
AND mr_hinnavalemid_read.aeg2 ))

                WHEN ((SELECT top 1 ale FROM mr_hinnavalemid_read
                INNER JOIN artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
                INNER JOIN tell_tellimused ON
tell_tellimused.number=@NUMBER
                WHERE mr_hinnavalemid_read.klass=artiklid.klass AND
mida='0'
                AND mr_hinnavalemid_read.kood=(SELECT top 1 hinnakiri FROM
tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER)
                AND
                ((tell_tellimused.aeg) BETWEEN mr_hinnavalemid_read.aeg1
AND mr_hinnavalemid_read.aeg2 )) IS NULL AND (SELECT top 1 ale FROM
mr_hinnavalemid_read
                INNER JOIN artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
                INNER JOIN tell_tellimused ON
tell_tellimused.number=@NUMBER
                WHERE mr_hinnavalemid_read.klass=artiklid.klass AND
mida='0'
                AND mr_hinnavalemid_read.kood=(SELECT top 1 hinnakiri FROM
tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER)
                AND
                (mr_hinnavalemid_read.aeg1 IS NULL AND
mr_hinnavalemid_read.aeg2 IS NULL )) IS NOT NULL)
                THEN (SELECT top 1 ale FROM mr_hinnavalemid_read
                INNER JOIN artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
                INNER JOIN tell_tellimused ON
tell_tellimused.number=@NUMBER
                WHERE mr_hinnavalemid_read.klass=artiklid.klass AND
mida='0'
                AND mr_hinnavalemid_read.kood=(SELECT top 1 hinnakiri FROM
tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER)
                AND
                (mr_hinnavalemid_read.aeg1 IS NULL AND
mr_hinnavalemid_read.aeg2 IS NULL )) END
-- when

```

```

-- ((select top 1 ale from mr_hinnavalemid_read
-- inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel
-- where mr_hinnavalemid_read.klass=artiklid.klass
-- and
-- ((select aeg from tell_tellimused with(nolock) where
number=@number) between aeg1 and aeg2)) is null and (select top 1 ale from
mr_hinnavalemid_read inner join artiklid ON
artiklid.kood=in_webshop_tell_tellimused_read.artikkel where
mr_hinnavalemid_read.klass=artiklid.klass and (aeg1 is null and aeg2 is
null)) is not null)
-- then (select top 1 ale from mr_hinnavalemid_read inner
join artiklid ON artiklid.kood=in_webshop_tell_tellimused_read.artikkel
where mr_hinnavalemid_read.klass=artiklid.klass and (aeg1 is null and aeg2
is null))END
-- ,case when EXISTS (select top 1 ale from mr_hinnavalemid_read
with(nolock) where mida='8' and kood=(select top 1 hinnakiri from
tell_tellimused with(nolock) where number=@number) and ((select aeg from
tell_tellimused with(nolock) where number=@number) between aeg1 and aeg2 )
and in_webshop_tell_tellimused_read.artikkel=artikkel or mida='8' and
kood=(select top 1 hinnakiri from tell_tellimused with(nolock) where
number=@number) and(aeg1 is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkel=artikkel)
-- then
-- '0'
-- ELSE

-- isnull((select top 1 ale from mr_hinnavalemid_read with(nolock) where
mida='0' and kood=(select top 1 hinnakiri from tell_tellimused with(nolock)
where number=@number) and ((select aeg from tell_tellimused with(nolock)
where number=@number) between aeg1 and aeg2 ) and
in_webshop_tell_tellimused_read.artikkel=artikkel or mida='0' and
kood=(select top 1 hinnakiri from tell_tellimused with(nolock) where
number=@number) and(aeg1 is null and aeg2 is null) and
in_webshop_tell_tellimused_read.artikkel=artikkel),
-- isnull((select top 1 ale from mr_hinnavalemid_read with(nolock)
where mida='0' and kood=(select top 1 hinnakiri from tell_tellimused
with(nolock) where number=@number) and ((select aeg from tell_tellimused
with(nolock) where number=@number) between aeg1 and aeg2 ) and klass=(select
top 1 klass from artiklid where
kood=in_webshop_tell_tellimused_read.artikkel)),(select top 1 ale from
mr_hinnavalemid_read with(nolock) where mida='0' and kood=(select top 1
hinnakiri from tell_tellimused with(nolock) where number=@number) and(aeg1
is null and aeg2 is null) and klass=(select top 1 klass from artiklid where
kood=in_webshop_tell_tellimused_read.artikkel))))
-- END
-- , isnull((select top 1 ale from mr_hinnavalemid_read
where mida='8' and artikkel=(select top 1 artikkel from
in_webshop_tell_tellimused_read where
in_webshop_tell_tellimused_read.artikkel=artikkel) and (((select aeg from
tell_tellimused where number=@number) between aeg1 and aeg2 ) or (aeg1 is

```

```

null and aeg2 is null)) and kood=(select hinnakiri from tell_tellimused
where number=@number)), 0)
    -- , isnull(hind,(select dbo.get_hind6(artikkel,(SELECT top
1 hinnakiri from tell_tellimused INNER JOIN mr_hinnaalemid_read ON
mr_hinnaalemid_read.artikkel=artikkel and mida='8' and (((select aeg from
tell_tellimused where number=@number) between aeg1 and aeg2 ) or (aeg1 is
null and aeg2 is null)) where number=@number), null, null, null,null,
null,null, null, null,null,0)))
    ,CASE WHEN EXISTS (SELECT top 1 ale FROM
mr_hinnaalemid_read WITH(nolock) WHERE mida='8'
    AND kood=(SELECT top 1 hinnakiri FROM
tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER)
    AND ((SELECT aeg FROM tell_tellimused
WITH(nolock) WHERE NUMBER=@NUMBER) BETWEEN aeg1 AND aeg2 )
    AND
in_webshop_tell_tellimused_read.artikkel=artikkel
    OR mida='8' AND kood=(SELECT top 1
hinnakiri FROM tell_tellimused WITH(nolock) WHERE NUMBER=@NUMBER) AND(aeg1
IS NULL AND aeg2 IS NULL) AND
in_webshop_tell_tellimused_read.artikkel=artikkel)
    THEN
    (SELECT dbo.get_hind6(artikkel,(SELECT top 1 hinnakiri
FROM tell_tellimused WHERE NUMBER=@NUMBER), NULL, NULL ,NULL,NULL,
NULL,NULL, (SELECT top 1 aeg FROM tell_tellimused WHERE NUMBER=@NUMBER),
NULL,NULL,0))

ELSE

(SELECT top 1 baashind FROM artiklid WHERE
kood=in_webshop_tell_tellimused_read.artikkel)
    END
    , kogus*isnull(hind,(SELECT top 1 baashind FROM artiklid
WITH(nolock) WHERE kood=artikkel))*(100-ISNULL(ale,0))/100
    , dbo.kesk_hind(artikkel,getdate())
    , isnull(nimetus,(SELECT top 1 nimi FROM artiklid
WITH(nolock) WHERE kood=artikkel))
    , isnull((SELECT top 1 kmkood FROM artiklid WITH(nolock)
WHERE kood=artikkel),(SELECT top 1 kmk_eesti FROM artikliklassid
WITH(nolock) WHERE kood=(SELECT TOP 1 klass FROM artiklid WHERE
kood=artikkel)))
    ,kommentaar, ROW_NUMBER() OVER(ORDER BY rn) , ROW_NUMBER()
OVER(ORDER BY rn )
    FROM in_webshop_tell_tellimused_read WITH(nolock) WHERE
NUMBER=@NUMBER

UPDATE tell_tellimused_read
SET kmkood=ISNULL((SELECT top 1 KMkood FROM artiklid
WITH(nolock) WHERE kood=tell_tellimused_read.artikkel),(SELECT kmk_eesti

```

```

FROM artikliklassid WITH(nolock) WHERE kood=(SELECT top 1 klass FROM
artiklid WITH(nolock) WHERE kood=tell_tellimused_read.artikkel)))
    WHERE NUMBER=@NUMBER AND kmkood IS NULL
    UPDATE tell_tellimused_read SET tkkm = dbo.summaKM
(yhikuhind,kmkood), rsum = dbo.summaKM(summa,kmkood) WHERE NUMBER=@NUMBER

    UPDATE tell_tellimused_read
    SET konto=ISNULL((SELECT top 1 konto_myyk FROM artiklid
WITH(nolock) WHERE kood=tell_tellimused_read.artikkel),(SELECT myyk_eestis
FROM artikliklassid WITH(nolock) WHERE kood=(SELECT top 1 klass FROM
artiklid WITH(nolock) WHERE kood=tell_tellimused_read.artikkel)))
    WHERE NUMBER=@NUMBER AND konto IS NULL

--EXEC dbo.tell_tellimused_renum @number
EXEC dbo.arvuta_tellimus @NUMBER
UPDATE tell_tellimused_read SET rv=rn WHERE NUMBER=@NUMBER
EXEC hooldus_vaba 'tellimus',@NUMBER

SET @koodid=@koodid+CONVERT(nvarchar,@NUMBER)

INSERT INTO kliendid (kood, nimi, address1, address2, address3,
nimi_lahetusel, lahaaddress1, lahaaddress2, lahaaddress3
, kontakt, email, telefon
, klient_tyyp, klass, regnr, kliendikaart
, cu, ts)
SELECT top 1
klient_kood, klient_nimi, address1, address2, address3,
klientnimi_lahetusel, lahaaddress1, lahaaddress2, lahaaddress3
, esindaja, email, telefon
, klient_tyyp, klient_klass, klient_regnr, klient_kliendikaart
, 'XML', GETDATE()
FROM in_webshop_tell_tellimused WITH(nolock) WHERE
NUMBER=@NUMBER
AND ISNULL(klient_kood, '') != ''
AND klient_kood NOT IN (SELECT kood FROM kliendid WITH(nolock))

INSERT INTO #results VALUES (@webid, 'ORDER', 0, 'OK', 'Orders')
END
ELSE
BEGIN
INSERT INTO #results VALUES (@webid, 'ORDER', 2,
'Duplicate', 'Orders')
END

SET @x=@x+1
END
FETCH NEXT FROM tellimused INTO @webid, @appkey
IF @@FETCH_STATUS = 0 SET @koodid=@koodid+';'
END
CLOSE tellimused

```

DEALLOCATE tellimused

--cleanup

--delete from in_webshop_tell_tellimused_klient where number in (select number from in_webshop_tell_tellimused where x=@key)

DELETE FROM in_webshop_tell_tellimused_read WHERE NUMBER IN (SELECT NUMBER FROM in_webshop_tell_tellimused WHERE x=@KEY)

DELETE FROM in_webshop_tell_tellimused WHERE x=@KEY

--sales orders from imago [EE software]

--vastuvotmine, kogused

DECLARE tellimused cursor FOR SELECT NUMBER, appkey FROM xml_in_imago_tellimused WHERE x=@KEY

OPEN tellimused

FETCH NEXT FROM tellimused INTO @webid, @appkey

WHILE @@FETCH_STATUS = 0

BEGIN

IF ISNULL(@appkey, '') != ISNULL(@appkey_setting, '')

BEGIN

INSERT INTO #results VALUES (@appkey, 'ORDER', 1, 'Incorrect key', 'Orders')

END

ELSE

BEGIN

SELECT @id_exist=COUNT(*) FROM tell_tellimused WHERE kliendi_tellimus=CONVERT(nvarchar(MAX),@webid)

IF @id_exist=0

BEGIN

--set @number=@webid

EXEC dbo.get_dok_number @moodul='tellimus',@seeria='DOC',@NUMBER = NULL, @cu='xmlcore', @aeg=@ag, @keel = 'default', @num =@NUMBER OUTPUT, @err = @err OUTPUT

UPDATE tell_tellimused SET

myyja=iif(isnull(z.myyja, '') != '', z.myyja, iif(isnull((SELECT myyja FROM kliendid WHERE kood=z.arvetasub), '') != '', (SELECT myyja FROM kliendid WHERE kood=z.arvetasub), iif(isnull((SELECT myyja FROM kliendid WHERE kood=z.klient_kood), '') != '', (SELECT myyja FROM kliendid WHERE kood=z.klient_kood), 'XML'))),

aeg=z.aeg,

klient_kood=z.klient_kood,

```

        arvetasub=z.arvetasub,
        tingimus=isnull(z.tingimus,(SELECT tingimus FROM
klientid WHERE kood=z.klient_kood)),
        ladu=isnull(z.ladu,'GAL'),
        klient_nimi=isnull(z.klient_nimi,(SELECT nimi FROM
klientid WHERE kood=z.klient_kood)),
        lahetusviis=isnull(z.tingimus,(SELECT tingimus FROM
klientid WHERE kood=z.klient_kood)),
        kommentaar=z.kommentaar,
        valuuta='EUR',
        kurssbv1=1,
        esindaja=isnull(z.esindaja,(SELECT kontakt FROM klientid
WHERE kood=z.klient_kood)),
        telefon=isnull(z.telefon,(SELECT telefon FROM klientid
WHERE kood=z.klient_kood)),
        aadress1=isnull(z.aadress1,(SELECT aadress1 FROM
klientid WHERE kood=z.klient_kood)),
        aadress2=isnull(z.aadress2,(SELECT aadress2 FROM
klientid WHERE kood=z.klient_kood)),
        aadress3=isnull(z.aadress3,(SELECT aadress3 FROM
klientid WHERE kood=z.klient_kood)),
        lahetusaadress1=isnull(z.lahaadress1,(SELECT lahaadress1
FROM klientid WHERE kood=z.klient_kood)),
        lahetusaadress2=isnull(z.lahaadress2,(SELECT lahaadress2
FROM klientid WHERE kood=z.klient_kood)),
        lahetusaadress3=isnull(z.lahaadress3,(SELECT lahaadress3
FROM klientid WHERE kood=z.klient_kood)),
        klient_nimi_lahetusel=isnull(z.klientnimi_lahetusel,(SELECT nimi_lahetusel
FROM klientid WHERE kood=z.klient_kood)),
        ts=getdate(),
        cu='XML',
        Field57=isnull(z.email,(SELECT email FROM klientid WHERE
kood=z.klient_kood)),
        objekt=isnull(z.objekt,(SELECT objekt FROM klientid
WHERE kood=z.klient_kood)),
        hinnakiri=(SELECT hinnakiri FROM klientid WHERE
kood=z.klient_kood),
        kliendi_tellimus=CONVERT(nvarchar(MAX),@webid)
        FROM (SELECT * FROM xml_in_imago_tellimused WHERE
NUMBER=@webid)z

        WHERE tell_tellimused.number=@NUMBER

        SELECT @maa=maa FROM klientid WHERE kood=(SELECT klient_kood
FROM xml_in_imago_tellimused WHERE NUMBER=@NUMBER)
/*
        insert into tell_tellimused (number, myyja, aeg, klient_kood,
arvetasub, tingimus, ladu, klient_nimi, lahetusviis
        , kommentaar, valuuta, kurssbv1
        ,esindaja, telefon, aadress1, aadress2, aadress3

```

```

        ,lahetusaadress1, lahetusaadress2, lahetusaadress3
        ,klient_nimi_lahetusel
        , ts, cu, Field57, objekt
        ,hinnakiri
    )
    SELECT @number

        ,iif(isnull('myyja','')!='',myyja,iif(isnull((select myyja
from kliendid where kood=xml_in_imago_tellimused.arvetasub),'')!='',(select
myyja from kliendid where
kood=xml_in_imago_tellimused.arvetasub),iif(isnull((select myyja from
kliendid where kood=xml_in_imago_tellimused.klient_kood),'')!='',(select
myyja from kliendid where kood=xml_in_imago_tellimused.klient_kood),'XML'))
        , aeg
        , klient_kood
        , arvetasub
        , isnull(tingimus,(select tingimus from kliendid where
kood=klient_kood))
        , isnull(ladu,'')
        , isnull(klient_nimi,(select nimi from kliendid where
kood=klient_kood))
        , isnull(tingimus,(select tingimus from kliendid where
kood=klient_kood))
        ,kommentaar
        , 'EUR', 1
        , isnull(esindaja,(select kontakt from kliendid where
kood=klient_kood))
        , isnull(telefon,(select telefon from kliendid where
kood=klient_kood))
        , isnull(aadress1,(select aadress1 from kliendid where
kood=klient_kood))
        , isnull(aadress2,(select aadress2 from kliendid where
kood=klient_kood))
        , isnull(aadress3,(select aadress3 from kliendid where
kood=klient_kood))
        , isnull(lahaadress1,(select lahaadress1 from kliendid where
kood=klient_kood))
        , isnull(lahaadress2,(select lahaadress2 from kliendid where
kood=klient_kood))
        , isnull(lahaadress3,(select lahaadress3 from kliendid where
kood=klient_kood))
        , isnull(klientnimi_lahetusel,(select nimi_lahetusel from
kliendid where kood=klient_kood))

        , GETDATE(), 'XML'
        , isnull(email,(select email from kliendid where
kood=klient_kood))
        , isnull(objekt,(select objekt from kliendid where
kood=klient_kood))
        ,(select hinnakiri from kliendid where kood=klient_kood)
    FROM xml_in_imago_tellimused where number=@number

```

```

*/
        SELECT * FROM in_xml_log ORDER BY rn DESC
        INSERT INTO tell_tellimused_read
        (NUMBER, artikkel, variant, konto, kogus, field8, yhikuhind,
summa, ostuhind, nimetus, kmkood, r_kommentaar, rn, rv)
        SELECT @NUMBER, artikkel, variant, (SELECT myyk_eestis FROM
artikliklassid WHERE kood=(SELECT klass FROM artiklid WHERE kood=artikkel)),
kogus
        , ale
        , isnull(hind, (SELECT baashind FROM artiklid WHERE
kood=artikkel))
        , kogus*isnull(hind, (SELECT baashind FROM artiklid WHERE
kood=artikkel))*(100-ISNULL(ale,0))/100
        , dbo.kesk_hind(artikkel, getdate()), nimetus
        , (SELECT kmk_eesti FROM artikliklassid WHERE kood=(SELECT
klass FROM artiklid WHERE kood=artikkel))
        , kommentaar, rn, rn
        FROM xml_in_imago_tellimused_read WHERE NUMBER=@webid

        UPDATE tell_tellimused_read
        SET kmkood=ISNULL((SELECT kmkood FROM artiklid WHERE
kood=tell_tellimused_read.artikkel), (SELECT kmk_eesti FROM artikliklassid
WHERE kood=(SELECT klass FROM artiklid WHERE
kood=tell_tellimused_read.artikkel)))
        WHERE NUMBER=@NUMBER AND kmkood IS NULL
        UPDATE tell_tellimused_read SET tkkm = dbo.summaKM
(yhikuhind, kmkood), rsum = dbo.summaKM(summa, kmkood) WHERE NUMBER=@NUMBER

        UPDATE tell_tellimused_read
        SET konto=ISNULL((SELECT konto_myyk FROM artiklid WHERE
kood=tell_tellimused_read.artikkel), (SELECT myyk_eestis FROM artikliklassid
WHERE kood=(SELECT klass FROM artiklid WHERE
kood=tell_tellimused_read.artikkel)))
        WHERE NUMBER=@NUMBER AND konto IS NULL

        EXEC dbo.tell_tellimused_renum @NUMBER
        EXEC dbo.arvuta_tellimus @NUMBER
        UPDATE tell_tellimused_read SET rv=rn WHERE NUMBER=@NUMBER
        EXEC hooldus_vaba 'tellimus', @NUMBER

        SET @koodid=@koodid+CONVERT(nvarchar, @NUMBER)

        INSERT INTO kliendid (kood, nimi, address1, address2, address3,
nimi_lahetusel, lahaaddress1, lahaaddress2, lahaaddress3
        , kontakt, email, telefon
        , klient_tyyp, klass, regnr, kliendikaart
        , cu, ts)
        SELECT top 1
        klient_kood, klient_nimi, address1, address2, address3,

```

```

klientnimi_lahetusel, lahaadress1, lahaadress2, lahaadress3
, esindaja, email, telefon
, klient_tyyp, klient_klass, klient_regnr, klient_kliendikaart
, 'XML', GETDATE()
    FROM xml_in_imago_tellimused WHERE NUMBER=@webid
AND ISNULL(klient_kood, '') != ''
AND klient_kood NOT IN (SELECT kood FROM kliendid)

    INSERT INTO #results VALUES (@webid, 'ORDER', 0, 'OK', 'Orders')
END
ELSE
BEGIN
    INSERT INTO #results VALUES (@webid, 'ORDER', 2,
'Duplicate', 'Orders')
END

    SET @x=@x+1
END
FETCH NEXT FROM tellimused INTO @webid, @appkey
IF @@FETCH_STATUS = 0 SET @koodid=@koodid+';'
END
CLOSE tellimused
DEALLOCATE tellimused

--cleanup
--delete from xml_in_imago_tellimused_klient where number in (select number
from xml_in_imago_tellimused where x=@key)
DELETE FROM xml_in_imago_tellimused_read WHERE NUMBER IN (SELECT NUMBER FROM
xml_in_imago_tellimused WHERE x=@KEY)
DELETE FROM xml_in_imago_tellimused WHERE x=@KEY

-----
-----
-
--tulemused valja

IF (SELECT COUNT(*) FROM #results)=0
    INSERT INTO #results VALUES (NULL, 'GENERAL ERROR', 99, 'No processable
data found', NULL)

SELECT @result1=
(SELECT RESULT AS "@Type", descr AS "@Desc", NUMBER AS "@docid", tyyp AS
"@doctype", submittype AS "@submit"
FROM #results FOR xml path ('Result'))

SET @result2='<?xml version="1.0"
encoding="UTF-8"?><results>'+CONVERT(nvarchar(MAX),@result1)+'</results>'

```

```
SELECT @result2
DROP TABLE #results

DELETE FROM in_xml_log WHERE datediff(DAY,ts_inserted,getdate())>=5
```

From:
<https://wiki.directo.ee/> - **Directo Help**

Permanent link:
<https://wiki.directo.ee/lv/procedures?rev=1600180391>

Last update: **2020/09/15 17:33**

